

PIEZOELECTRIC/ELECTROSTRICTIVE DEVICE AND
METHOD OF MANUFACTURING SAME

BACKGROUND OF THE INVENTION

5 Field of the Invention:

10 The present invention relates to a piezoelectric
/electrostrictive device which is provided with a movable
section to be operated on the basis of a displacement action
of a piezoelectric/electrostrictive element, or a
piezoelectric/electrostrictive device which is capable of
detecting displacement of a movable section by the aid of a
piezoelectric/electrostrictive element, and a method for
producing the same. In particular, the present invention
relates to a piezoelectric/electrostrictive device which is
excellent in strength, shock resistance, and moisture
resistance and which makes it possible to efficiently
operate a movable section to a great extent, and a method
for producing the same.

Description of the Related Art:

20 ~~Recently, a displacement element, which makes it~~
possible to adjust the optical path length and the position
in an order of submicron, is required, for example, in the
fields of the optical science, the magnetic recording, and
the precision machining. Development is advanced for the
25 displacement element based on the use of the displacement
brought about by the inverse piezoelectric effect or the
~~electrostrictive effect caused when a voltage is applied to~~

Ins.
Bq
end

~~a piezoelectric/electrostrictive material (for example, a ferroelectric material).~~

As shown in FIG. 53, for example, those hitherto disclosed as such a displacement element include a piezoelectric actuator comprising a fixation section 404, a movable section 406, and a beam section 408 for supporting them which are formed in an integrated manner with a hole 402 provided through a plate-shaped member 400 composed of a piezoelectric/electrostrictive material and with an electrode layer 410 provided on the beam section 408 (see, for example, Japanese Laid-Open Patent Publication No. 10-136665).

The piezoelectric actuator is operated such that when a voltage is applied to the electrode layer 410, the beam section 408 makes extension and contraction in a direction along a line obtained by connecting the fixation section 404 and the movable section 406 in accordance with the inverse piezoelectric effect or the electrostrictive effect. Therefore, the movable section 406 can perform circular arc-shaped displacement or rotational displacement in the plane of the plate-shaped member 400.

On the other hand, Japanese Laid-Open Patent Publication No. 63-64640 discloses a technique in relation to an actuator based on the use of a bimorph. In this technique, electrodes for the bimorph are provided in a divided manner. The divided electrodes are selectively driven, and thus the highly accurate positioning is

performed at a high speed. This patent document (especially in FIG. 4) discloses a structure in which, for example, two bimorphs are used in an opposed manner.

However, the piezoelectric actuator described above involves such a problem that the amount of operation of the movable section 406 is small, because the displacement in the direction of extension and contraction of the piezoelectric/electrostrictive material (i.e., in the in-plane direction of the plate-shaped member 400) is transmitted to the movable section 406 as it is.

All of the parts of the piezoelectric actuator are made of the piezoelectric/electrostrictive material which is a fragile material having a relatively heavy weight. Therefore, the following problems arise. That is, the mechanical strength is low, and the piezoelectric actuator is inferior in handling performance, shock resistance, and moisture resistance. Further, the piezoelectric actuator itself is heavy, and its operation tends to be affected by harmful vibrations (for example, residual vibration and noise vibration during high speed operation).

In order to solve the problems described above, it has been suggested that the hole 402 is filled with a filler material having flexibility. However, it is clear that the amount of displacement, which is brought about by the inverse piezoelectric effect or the electrostrictive effect, is decreased even when the filler material is merely used.

SUMMARY OF THE INVENTION

5 The present invention has been made taking the foregoing problems into consideration, an object of which is to provide a piezoelectric/electrostrictive device and a method for producing the same which make it possible to obtain a displacement element that is scarcely affected by harmful vibration and capable of high speed response with high mechanical strength while being excellent in handling performance, shock resistance, and moisture resistance, making it possible to realize a long life time of a device, and improve the handling performance of the device and the attachment performance for parts to be attached to the movable section or the fixation performance of the device, so that the movable section may be greatly displaced at a relatively low voltage, and it is possible to achieve a high speed of the displacement action of the device, especially of the movable section (realization of a high resonance frequency), as well as a sensor element which makes it possible to accurately detect vibration of the movable section.

10 20 According to the present invention, there is provided a piezoelectric/electrostrictive device comprising at least an actuator section including a stacked type piezoelectric /electrostrictive element secured onto a thin plate section made of metal with an adhesive intervening therebetween; wherein an actuator film of the stacked type piezoelectric/electrostrictive element, which is composed of

piezoelectric/electrostrictive layers and electrode films,
is constructed by a multilayered member including at least
three layers or more.

Accordingly, the thin plate section can be displaced to
a great extent even when the areal size of the stacked type
piezoelectric/electrostrictive element is not widened on the
plane. Further, the piezoelectric/electrostrictive device
is excellent in strength and toughness, because the thin
plate section is made of metal. Further, it is possible to
correspond to the quick displacement action.

In other words, according to the present invention, it
is possible to sufficiently respond to any variation of the
environment of use and any severe state of use. The
piezoelectric/electrostrictive device is excellent in shock
resistance, and it is possible to realize a long life time
of the piezoelectric/electrostrictive device and improve the
handling performance of the piezoelectric /electrostrictive
device. Further, the thin plate section can be greatly
displaced at a relatively low voltage. The rigidity of the
thin plate section is high, the film thickness of the
actuator film is thick, and the rigidity thereof is high.
Therefore, it is possible to achieve a high speed of the
displacement action of the thin plate section (realize a
high resonance frequency).

It is preferable that the plurality of electrode films,
which are included in the multilayered member for
constructing the piezoelectric/electrostrictive element, are

stacked to have alternate end surfaces, and they are connected so that an identical voltage is applied to every other layer. It is preferable that the actuator film is composed of the multilayered member having ten layers or less. It is preferable that the actuator film is formed by means of a multilayer printing method. Further, it is preferable that a positional discrepancy in an in-plane direction, which possibly occurs on a perpendicular projection plane of each of the electrode films disposed as every other layer, is not more than 50 μm . It is preferable that the adhesive has a thickness of not more than 15 μm .

~~In the present invention, it is also preferable that an underlying layer is formed on a surface of the piezoelectric/electrostrictive element opposed to the thin plate section. It is also preferable that one or more holes or recesses are formed at least at a portion of the thin plate section at which the piezoelectric/electrostrictive element is formed. In this arrangement, the adhesive enters the interior of the hole or the recess, and hence the adhesion area is substantially increased. Further, it is possible to achieve a thin thickness of the adhesive. It is also preferable that at least a portion of a surface of the thin plate section, on which the piezoelectric/electrostrictive element is formed, is a rough surface. In this arrangement, the adhesion area is substantially increased, and hence the adhesion can be tightly effected.~~

According to another aspect of the present invention, there is provided a piezoelectric/electrostrictive device comprising a pair of mutually opposing thin plate sections made of metal and a fixation section for supporting the thin plate sections, and including an actuator section with a stacked type piezoelectric/electrostrictive element fixed on at least one of the thin plate sections by the aid of an adhesive; wherein the stacked type piezoelectric/electrostrictive element is composed of a plurality of piezoelectric/electrostrictive layers and electrode films; and the electrode films, which contact with upper and lower surfaces of the respective piezoelectric/electrostrictive layers, are alternately led to opposite end surfaces, and end surface electrodes, which electrically connect the respective electrode films alternately led to the opposite end surfaces, are electrically connected to terminals which are provided on a surface of an outermost layer of the piezoelectric/electrostrictive layer and which are arranged while being separated from each other by a predetermined distance respectively. Accordingly, the driving signal can be easily supplied, and the detection signal can be easily obtained with respect to the stacked piezoelectric/electrostrictive element. It is possible to realize the formation of the stacked type piezoelectric/electrostrictive element on the thin plate section.

In the invention described above, it is also preferable that the stacked type piezoelectric/electrostrictive element has a substantially rectangular parallelepiped-shaped configuration. It is preferable that the predetermined distance between the terminals is not less than 50 μm . It is also preferable that at least one of the terminals and one of the end surface electrodes are electrically connected with each other with an electrode film having a film thickness which is thinner than those of the terminal and the end surface electrode.

10
960069-092800
MS. B11
According to still another aspect of the present invention, there is provided a piezoelectric/electrostrictive device comprising a pair of mutually opposing thin plate sections, and a fixation section for supporting the thin plate sections; and one or more piezoelectric/electrostrictive elements arranged on at least one thin plate section of the pair of thin plate sections; wherein a minimum resonance frequency of the device structure, which is obtained when an object member having a size substantially equivalent to that of the fixation section exists between open ends of the pair of thin plate sections, is not less than 20 kHz, and a relative displacement amount between the object member and the fixation section is not less than 0.5 μm at a substantial applied voltage of 30 V at a frequency which is not more than 1/4 of the resonance frequency.

Accordingly, it is possible to greatly displace the

pair of thin plate sections. Further, it is possible to achieve realization of a high speed (realization of a high resonance frequency) for the displacement action of the device, especially of the pair of thin plate sections.

5 Furthermore, it is possible to obtain a displacement element which is scarcely affected by harmful vibration, which is capable of performing high speed response, which has high mechanical strength, and which is excellent in handling performance, shock resistance, and moisture resistance. Moreover, it is possible to obtain a sensor element which makes it possible to accurately detect the vibration of the movable section.

At least the thin plate section and the fixation section may be constructed by using ceramics or metal. The respective components may be constructed with ceramic materials, or they may be constructed with metal materials. Further, the respective components may be constructed as a hybrid structure obtained by combining those produced from ceramic and metal materials.

20 It is preferable that when an adhesive intervenes between the piezoelectric/electrostrictive element and the thin plate section, the adhesive has a thickness which is not more than 10 % of a thickness of the piezoelectric /electrostrictive element. It is preferable that when one
25 or more piezoelectric/electrostrictive elements are arranged on one thin plate section of the pair of thin plate sections, a thickness of the one thin plate section is

thicker than a thickness of the other thin plate section.

It is preferable that when the object member intervenes between the open ends of the pair of thin plate sections, then a distance concerning the pair of thin plate sections between a boundary portion with respect to the object member and a boundary portion with respect to the fixation section is not less than 0.4 mm and not more than 2 mm, and each of the pair of thin plate sections has a thickness which is not less than 10 μm and not more than 100 μm .

It is preferable that the piezoelectric/electrostrictive element is constructed by multilayered member including at least three or more actuator films, which is composed of piezoelectric/electrostrictive layers and electrode films. In this arrangement, it is preferable that the actuator film is composed of the multilayered member having ten layers or less. Further, it is preferable that the piezoelectric/electrostrictive layer has a thickness which is not less than 5 μm and not more than 30 μm . It is preferable that the electrode film has a thickness which is not less than 0.5 μm and not more than 20 μm .

It is preferable that the plurality of electrode films, which are included in the multilayered member for constructing the piezoelectric/electrostrictive element, are stacked alternately, and they are connected so that an identical voltage is applied to every other layer.

Especially, when the thin plate section is made of

metal, the piezoelectric/electrostrictive element is formed such that only the piezoelectric/electrostrictive layer of the first layer, or the electrode film of the first layer and the piezoelectric/electrostrictive layer of the first layer, of the multilayered member for constructing the piezoelectric/electrostrictive element make contact with the thin plate section. By doing so, it is possible to avoid the phenomenon of short circuit formation between the different electrodes.

It is also preferable that one of ends of the electrode layer is formed at a position not including at least the fixation section as viewed in plan view. It is also preferable that an end of the multilayered member for constructing the piezoelectric/electrostrictive element is formed at a position not including at least the fixation section as viewed in plan view.

It is preferable that $(1 - L_b/L_a)$ is not less than 0.4, provided that L_a represents a shortest distance concerning the pair of thin plate sections between a boundary portion with respect to the object member and a boundary portion with respect to the fixation section, and L_b represents a shortest distance of distances from the boundary portion between the thin plate section and one of the object member and the fixation section on which the multilayered member for constructing the piezoelectric/electrostrictive element is not formed, to an end of the electrode film. More preferably $(1 - L_b/L_a)$ is 0.5 to 0.8.

It is preferable that when the thin plate section is made of metal, the thin plate section is composed of a metal plate subjected to a cold rolling process.

5 It is also preferable that an adhesive, which has a thickness of not less than 0.1 μm and not more than 30 μm , is allowed to intervene between the thin plate section and the multilayered member for constructing the piezoelectric/electrostrictive element. In this arrangement, the adhesive may be organic resin, or the adhesive may be glass, brazing material, or solder.

10 ~~It is also preferable that an underlying layer is~~
15 ~~formed on a surface of the multilayered member opposed to~~
~~the thin plate section. It is also preferable that one or~~
~~more holes or recesses are formed at least at a portion of~~
~~the thin plate section at which the multilayered member is~~
~~formed. In this arrangement, the adhesive enters the inside~~
~~of the hole and the recess, and hence the adhesion area is~~
~~substantially increased. Further, it is possible to use a~~
~~thin thickness of the adhesive. It is also preferable that~~
20 ~~at least a portion of a surface of the thin plate section,~~
~~on which the multilayered member is formed, is a rough~~
~~surface. In this arrangement, the adhesion area is~~
~~substantially increased, and hence the adhesion can be~~
~~tightly effected. It is preferable that an adhesive, which~~
25 ~~has a thickness of not less than 0.1 μm and not more than 30~~
 ~~μm , is allowed to intervene between the thin plate section~~
~~and at least the fixation section. In this arrangement, the~~

Ins.
Blz
end

~~adhesive may be organic resin, or the adhesive may be glass,
brazing material, or solder.~~

5 It is preferable that a stick-out shape of the adhesive, which protrudes from an opposing portion between the thin plate section and at least the fixation section, has a curvature. In this arrangement, the inner wall of the fixation section and the inner wall of each of the thin plate sections are used as the adhesion surface. Therefore, the adhesion area is increased, and it is possible to increase the adhesion strength. Further, the concentration of the stress, which would be otherwise caused on the joined portion (angular portion) between the inner wall of the fixation section and the inner wall of each of the thin plate sections, can be effectively dispersed.

10 09672069-092800

15 It is preferable that when an object member intervenes between open ends of the pair of thin plate sections, at least an angular portion of the fixation section opposed to the object member is chamfered. In this arrangement, the stick-out amount of the adhesive can be stabilized by

20 appropriately adjusting the chamfering angle and the radius of curvature. Further, it is possible to suppress the local dispersion of the adhesion strength. Thus, it is possible to improve the yield. It is preferable that when the thin plate section is manufactured by means of stamping for a

25 metal plate, a burr, which is brought about by the stamping, is directed outwardly, considering the handling performance and the direction of adhesion of the respective members.

INS-1
B13

5 According to still another aspect of the present invention, there is provided a method for producing a piezoelectric/electrostrictive device comprising a pair of mutually opposing thin plate sections, and a fixation section for supporting the thin plate sections; and one or more piezoelectric/electrostrictive elements arranged on at least one thin plate section of the pair of thin plate sections; the method comprising the steps of preparing a plurality of thin plates for forming at least the thin plate sections thereafter, the piezoelectric/electrostrictive element, and a support substrate; securing the piezoelectric /electrostrictive element to at least one of the thin plates by the aid of a first adhesive; securing the plurality of thin plates to the support substrate by the aid of a second adhesive to manufacture a master device block including the plurality of thin plates disposed opposingly; and dividing the master device block into a plurality of chips to manufacture individuals of the piezoelectric/electrostrictive devices.

10 09672069-152800

15

20 According to still another aspect of the present invention, there is provided a method for producing a piezoelectric/electrostrictive device comprising a pair of mutually opposing thin plate sections, and a fixation section for supporting the thin plate sections; and one or

25 more piezoelectric/electrostrictive elements arranged on at least one thin plate section of the pair of thin plate sections; the method comprising the steps of preparing a

INS.
B13
CMLd.

plurality of thin plates for forming at least the thin plate sections thereafter, the piezoelectric/electrostrictive element, and a support substrate; securing the plurality of thin plates to the support substrate by the aid of a second adhesive to manufacture a master device block including the plurality of thin plates disposed opposingly; securing the piezoelectric/electrostrictive element to at least one of the thin plates by the aid of a first adhesive; and dividing the master device block into a plurality of chips to manufacture individuals of the piezoelectric/electrostrictive devices.

According to the production methods as described above, it is possible to easily produce the piezoelectric /electrostrictive device in which the pair of thin plate sections can be greatly displaced, and it is possible to achieve realization of the high speed (realization of the high resonance frequency) of the device, especially of the displacement action of the pair of thin plate sections.

It is also preferable in the production method described above that when an object member intervenes between open ends of the pair of thin plate sections of the piezoelectric/electrostrictive device to be produced; the support substrate is a rectangular annular structure having a portion to be formed into at least the object member thereafter, and a portion to be formed into the fixation section thereafter.

Alternatively, it is also preferable in the production

method described above that when an object member does not intervene between open ends of the pair of thin plate sections of the piezoelectric/electrostrictive device to be produced; the support substrate is a rectangular annular structure having a portion for supporting the open ends (portion to substantially define the thickness of a portion for allowing at least the object member to intervene thereafter), and a portion to be formed into the fixation section thereafter.

The first adhesive and/or the second adhesive may be organic resin, or the first adhesive and/or the second adhesive may be glass, brazing material, or solder. On the other hand, the thin plates and/or the support substrate may be made of metal.

It is preferable that when the step of dividing the master device block includes a treatment for cutting the master device block along predetermined cutting lines; the cutting is performed in substantially the same direction as a displacement direction of the pair of thin plate sections.

20 INS. B14 > ~~Further, it is also preferable that the production~~
method according to the present invention further comprises
the step of forming an underlying layer on a surface of the
piezoelectric/electrostrictive element opposed to the thin
plate before securing the piezoelectric/electrostrictive
element to the thin plate by the aid of the first adhesive.
It is also preferable that the production method according
to the present invention further comprises the step of

forming one or more holes or recesses at least at a portion
of the thin plate to which the
piezoelectric/electrostrictive element is secured.

It is also preferable that at least a portion of a
surface of the thin plate, to which the
piezoelectric/electrostrictive element is secured, is
roughened. It is also preferable to form a curvature for a
stick-out shape of the second adhesive protruding from an
opposing portion between the thin plate and the support
substrate.

It is also preferable to chamfer mutually opposing
angular portions of the support substrate of the master
device block. It is also preferable that the method further
comprises the step of manufacturing the thin plate by means
of stamping for a metal plate; wherein when the master
device block is produced by combining the thin plate with
the support substrate, a burr, which is brought about on the
thin plate due to the stamping, is directed outwardly to
produce the master device block.

Therefore, the piezoelectric/electrostrictive device
according to the present invention can be utilized as the
active device including, for example, various transducers,
various actuators, frequency region functional parts
(filters), transformers, vibrators, resonators, oscillators,
and discriminators for the communication and the power
generation, as well as the sensor element for various
sensors including, for example, ultrasonic sensors,

acceleration sensors, angular velocity sensors, shock sensors, and mass sensors. Especially, the piezoelectric/electrostrictive device according to the present invention can be preferably utilized for various actuators to be used for the mechanism for adjusting the displacement and the positioning and for adjusting the angle for various precision parts such as those of optical instruments and precision mechanical equipments.

The above and other objects, features, and advantages of the present invention will become more apparent from the following description when taken in conjunction with the accompanying drawings in which a preferred embodiment of the present invention is shown by way of illustrative example.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows a perspective view illustrating an arrangement of a piezoelectric/electrostrictive device according to a first embodiment;

FIG. 2 shows a perspective view illustrating a first modified embodiment of the piezoelectric/electrostrictive device according to the first embodiment;

FIG. 3 shows a perspective view illustrating a second modified embodiment of the piezoelectric/electrostrictive device according to the first embodiment;

FIG. 4 shows a perspective view illustrating a third modified embodiment of the piezoelectric/electrostrictive device according to the first embodiment;

FIG. 5 shows a perspective view illustrating a fourth modified embodiment of the piezoelectric/electrostrictive device according to the first embodiment;

FIG. 6 shows a perspective view illustrating a fifth modified embodiment of the piezoelectric/electrostrictive device according to the first embodiment;

FIG. 7 shows a perspective view illustrating another embodiment of the piezoelectric/electrostrictive device concerning the fifth modified embodiment;

FIG. 8 shows a perspective view illustrating a sixth modified embodiment of the piezoelectric/electrostrictive device according to the first embodiment;

FIG. 9 shows a perspective view illustrating a seventh modified embodiment of the piezoelectric/electrostrictive device according to the first embodiment;

FIG. 10 shows, with partial omission, another embodiment of the piezoelectric/electrostrictive element;

FIG. 11 shows, with partial omission, still another embodiment of the piezoelectric/electrostrictive element;

FIG. 12 illustrates a situation in which both of the piezoelectric/electrostrictive elements do not make the displacement action in the piezoelectric/electrostrictive device according to the first embodiment;

FIG. 13A shows a waveform illustrating a voltage waveform to be applied to the first piezoelectric /electrostrictive element;

FIG. 13B shows a waveform illustrating a voltage

waveform to be applied to the second piezoelectric /electrostrictive element;

FIG. 14 illustrates a situation in which the piezoelectric/electrostrictive element makes the displacement action in the piezoelectric/electrostrictive device according to the first embodiment;

FIG. 15 shows a perspective view illustrating an arrangement in which a second piezoelectric/electrostrictive device is secured to a movable section of a first piezoelectric/electrostrictive device;

FIG. 16A illustrates a process for stacking necessary ceramic green sheets in a first production method;

FIG. 16B illustrates a state in which a ceramic green stack is formed;

FIG. 17A illustrates a state in which the ceramic green stack is sintered to provide a ceramic stack;

FIG. 17B illustrates a state in which piezoelectric/electrostrictive elements, which are constructed as separate members, are glued to the surfaces of metal plates to serve as thin plate sections respectively;

FIG. 18 illustrates a state in the first production method in which the metal plate is glued to the ceramic stack to provide a hybrid stack;

FIG. 19 illustrates a state in which the hybrid stack is cut along predetermined cutting lines to provide the piezoelectric/electrostrictive device according to the first

embodiment;

FIG. 20A illustrates a process for stacking necessary ceramic green sheets in a second production method;

FIG. 20B illustrates a state in which a ceramic green stack is formed;

FIG. 21A illustrates a state in which the ceramic green stack is sintered to provide a ceramic stack, and then a hole is filled with a filler material;

FIG. 21B illustrates a state in which metal plates to serve as thin plate sections respectively are glued to the ceramic stack to provide a hybrid stack;

FIG. 22 illustrates a state in which piezoelectric /electrostrictive elements, which are constructed as separate members, are glued to the surfaces of the metal plates of the hybrid stack;

FIG. 23 illustrates a state in which the piezoelectric/electrostrictive device according to the first embodiment is produced by cutting the hybrid stack along predetermined cutting lines;

FIG. 24 shows a perspective view illustrating an arrangement of a piezoelectric/electrostrictive device according to a second embodiment;

FIG. 25 shows a perspective view illustrating another arrangement of the piezoelectric/electrostrictive device according to the second embodiment;

FIG. 26 shows a magnified view illustrating an exemplary arrangement of a stacked type piezoelectric

/electrostrictive element;

FIG. 27 shows a magnified view illustrating a preferred exemplary arrangement of the stacked type piezoelectric /electrostrictive element shown in FIG. 26;

5 FIG. 28 shows a magnified view illustrating another exemplary arrangement of a stacked type piezoelectric /electrostrictive element;

FIG. 29 shows a magnified view illustrating a preferred exemplary arrangement of the stacked type piezoelectric /electrostrictive element shown in FIG. 28;

FIG. 30 shows a perspective view illustrating still another arrangement of the piezoelectric/electrostrictive device according to the second embodiment;

FIG. 31 illustrates the preferred dimensional relationship concerning the piezoelectric/electrostrictive device according to the second embodiment;

FIG. 32 illustrates a state in a third production method in which a rectangular hole is bored through a central portion of a stainless steel plate to manufacture a substrate having a rectangular annular structure;

FIG. 33 illustrates a state in which an adhesive is formed on the first stainless steel thin plate;

FIG. 34 illustrates a state in which the stacked type piezoelectric/electrostrictive element is glued to the first stainless steel thin plate with the adhesive intervening therebetween;

FIG. 35 illustrates a state in which the first and

second stainless steel thin plates are glued to the substrate by the aid of the adhesive;

FIG. 36 illustrates a state in which a manufactured master device block is cut;

5 FIG. 37 illustrates a state in a fourth production method in which a rectangular hole is bored through a central portion of a stainless steel plate to manufacture a substrate having a rectangular annular structure, and first and second stainless steel thin plates are glued to the substrate by the aid of an adhesive;

FIG. 38 illustrates a state in which the first and second stainless steel thin plates are glued by the aid of the adhesive;

FIG. 39 illustrates a state in which the adhesive is formed on the first stainless steel thin plate;

FIG. 40 illustrates a state in which a stacked type piezoelectric/electrostrictive element is glued to the first stainless steel thin plate by the aid of the adhesive;

FIG. 41 illustrates a state in which first and second stainless steel thin plates are glued to another exemplary substrate by the aid of an adhesive;

FIG. 42 illustrates an example in which bumps are provided at portions of respective stainless steel thin plates to which a support section to be formed into a movable section thereafter and a support section to be formed into a fixation section thereafter are glued respectively;

FIG. 43 illustrates an example in which bumps are provided at portions of respective stainless steel thin plates to which a support section to be formed into a fixation section thereafter is glued;

5 FIG. 44 illustrates an example in which no bump is provided on respective stainless steel thin plates;

FIG. 45 illustrates an example in which projections for forming compartments for gluing are provided at portions of respective stainless steel thin plates to which a support section to be formed into a movable section thereafter and a support section to be formed into a fixation section thereafter are glued respectively;

FIG. 46 illustrates a case concerning the example shown in FIG. 42, in which the size of the support section to be formed into the fixation section, especially the areal size of the surface of the stainless steel thin plate opposed to the bump is larger than the areal size of the bump;

FIG. 47 illustrates a first technique (to define holes through a stainless steel thin plate);

20 FIG. 48 illustrates a second technique (to roughen the surfaces of a stainless steel thin plate and a stacked type piezoelectric/electrostrictive element);

FIG. 49 illustrates a third technique (to provide a curvature for stick-out portions of an adhesive);

25 FIG. 50 illustrates a fourth technique (to chamfer angular portions of respective support sections);

FIG. 51 illustrates a fifth technique (to direct burrs

outwardly);

FIG. 52 illustrates a sixth technique (to change the thickness for respective stainless steel thin plates); and

FIG. 53 shows an arrangement of a piezoelectric/electrostrictive device concerning an illustrative conventional technique.

~~DESCRIPTION OF THE PREFERRED EMBODIMENTS~~

Explanation will be made below with reference to FIGS. 1 to 52 for illustrative embodiments of the piezoelectric/electrostrictive device and the production method for the same according to the present invention.

It is noted that the piezoelectric/electrostrictive device resides in a concept which includes the element for mutually converting the electric energy and the mechanical energy by the aid of the piezoelectric/electrostrictive element. Therefore, the piezoelectric/electrostrictive device is most preferably used as the active element such as various actuators and vibrators, especially as the displacement element based on the use of the displacement brought about by the inverse piezoelectric effect or the electrostrictive effect. Additionally, the piezoelectric/electrostrictive device is also preferably used as the passive element such as acceleration sensor elements and shock sensor elements.

As shown in FIG. 1, the piezoelectric/electrostrictive device 10A according to the first embodiment has a substrate

14 which has a lengthy rectangular parallelepiped-shaped configuration as a whole and which has a hole 12 provided at an approximately central portion in the major axis direction thereof.

5 The substrate 14 comprises a pair of mutually opposing thin plate sections 16a, 16b, a movable section 20, and a fixation section 22 for supporting the pair of thin plate sections 16a, 16b and the movable section 20.

Piezoelectric/electrostrictive elements 24a, 24b are formed at respective parts of at least the thin plate sections 16a, 16b respectively.

10 The substrate 14 may be constructed by using ceramics or metal for the entire substrate 14. Alternatively, the substrate 14 may have a hybrid structure obtained by combining those produced with ceramic and metal materials. Further, those adoptable for constructing the substrate 14 include, for example, a structure in which respective parts are glued to one another with an adhesive such as organic resin and glass, and a metal integrated structure which is
15 integrated into one unit, for example, by means of brazing, soldering, eutectic bonding, or welding.

20 In the first embodiment, the substrate 14 has a hybrid structure in which the pair of thin plate sections 16a, 16b are made of metal, and the other parts, i.e., the movable
25 section 20 and the fixation section 22 are made of ceramics. Specifically, the thin plate sections 16a, 16b made of metal are secured by an adhesive 200 to respective side surfaces

of the movable section 20 and the fixation section 22 made of ceramics. It is a matter of course that all of the thin plate sections 16a, 16b, the movable section 20, and the fixation section 22 may be made of metal.

5
Ins. B16
The ~~piezoelectric/electrostrictive elements 24a, 24b~~ are prepared as separate members as described later on, and the prepared piezoelectric/electrostrictive elements 24a, 24b are stuck to the substrate 14 with an adhesive such as organic resin or glass or by means of brazing, soldering, or eutectic bonding. Alternatively, the piezoelectric /electrostrictive elements 24a, 24b are directly formed on the substrate 14 by using the film formation method not by using the sticking method described above. In the first embodiment, the piezoelectric/electrostrictive elements 24a, 24b are secured onto the thin plate sections 16a, 16b by the aid of an adhesive 202 respectively.

10
09672069-032800
15
20
25
The piezoelectric/electrostrictive device 10A includes the hole 12 having, for example, a rectangular configuration which is formed by both inner walls of the pair of thin plate sections 16a, 16b, an inner wall 20a of the movable section 20, and an inner wall 22a of the fixation section 22. The piezoelectric/electrostrictive device 10A is constructed such that the movable section 20 is displaced in accordance with the driving of the piezoelectric /electrostrictive element or elements 24a and/or 24b, or the displacement of the movable section 20 is detected by the piezoelectric/electrostrictive element or elements 24a

and/or 24b.

INS.
B17

~~Each of the piezoelectric/electrostrictive elements~~
24a, 24b comprises a piezoelectric/electrostrictive layer
26, and a pair of electrodes 28, 30 formed on both sides of
the piezoelectric/electrostrictive layer 26. One electrode
28 of the pair of electrodes 28, 30 is formed at least on
~~each of the pair of thin plate sections 16a, 16b.~~

10 9672069-032300
15
20
25

In the embodiment shown in FIG. 1, respective forward
end surfaces of the pair of electrodes 28, 30 and the
piezoelectric/electrostrictive layer 26 for constructing the
piezoelectric/electrostrictive element 24a, 24b are
substantially aligned. A substantial driving portion 18 of
the piezoelectric/electrostrictive element 24a, 24b (portion
at which the pair of electrodes 28, 30 are overlapped with
each other with the piezoelectric/electrostrictive layer 26
interposed therebetween) is continuously formed over a range
from a part of the outer circumferential surface of the
fixation section 22 to a part of the outer circumferential
surface of the thin plate section 16a, 16b. Especially, in
this embodiment, the respective forward end surfaces of the
pair of electrodes 28, 30 are located at the positions
slightly deviated rearwardly from the inner wall 20a of the
movable section 20. Of course, the piezoelectric /electro-
strictive element 24a, 24b may be formed such that the
substantial driving portion 18 is located over a range from
a part of the movable section 20 to a part of the thin plate
section 16a, 16b.

As shown in FIG. 1, the piezoelectric/electrostrictive device 10A according to the first embodiment described above includes mutually opposing end surfaces 36a, 36b which are formed in the movable section 20. Each of the end surfaces 36a, 36b is a surface substantially parallel to the side surface of the movable section 20, i.e., the surface for forming the element. The respective end surfaces 36a, 36b are separated from each other from the upper surface of the movable section 20 to the hole 12. In this arrangement, as shown in FIG. 12, for example, it is preferable that the distances D_a , D_b , which range from the central axis n of the movable section 20 to the respective end surfaces 36a, 36b, are substantially equal to one another.

As shown in FIG. 1, for example, a gap (air) 38 may be allowed to intervene between the end surfaces 36a, 36b. Alternatively, as in a piezoelectric/electrostrictive device 10Ag according to a seventh modified embodiment shown in FIG. 9 or as shown in FIG. 12, a member different from the constitutive member of the movable section 20, for example, a member 40 composed of, for example, resin or the like may be allowed to intervene between the end surfaces 36a, 36b.

Ins. B18
~~In the piezoelectric/electrostrictive device 10A~~ according to the first embodiment, the voltage is applied to the pair of electrodes 28, 30 via terminals (pads) 32, 34 of the respective electrodes 28, 30 formed on the both side surfaces (element formation surfaces) of the fixation section 22 respectively. ~~The respective terminals 32, 34~~

INS' B18 cancelled.

are positioned as follows. That is, the terminal 32 corresponding to the first electrode 28 is formed at the position deviated toward the rearward end of the fixation section 22. The terminal 34 corresponding to the second electrode 30 disposed on the side of the external space is formed at the position deviated toward the inner wall 22a of the fixation section 22.

In this embodiment, the piezoelectric/electrostrictive device 10A can be individually fixed by utilizing the surfaces respectively different from the surfaces on which the terminals 32, 34 are arranged. As a result, it is possible to obtain the high reliability for both of the fixation of the piezoelectric/electrostrictive device 10A and the electric connection between the circuit and the terminals 32, 34. In this arrangement, the electric connection between the terminals 32, 34 and the circuit is made, for example, by means of the flexible printed circuit (also referred to as FPC), the flexible flat cable (also referred to as FFC), and the wire bonding.

Structures other than the structure shown in FIG. 1 are available to construct the piezoelectric/electrostrictive element 24a, 24b. That is, as in a piezoelectric /electrostrictive device 10Aa according to a first modified embodiment shown in FIG. 2, it is also preferable that the respective forward ends of the pair of electrodes 28, 30 for constructing the piezoelectric/electrostrictive element 24a, 24b are aligned, and only the forward end of the

piezoelectric/electrostrictive layer 26 is allowed to protrude toward the movable section 20. Alternatively, as in a piezoelectric/electrostrictive device 10Ab according to a second modified embodiment shown in FIG. 3, it is also preferable that the respective forward ends of the first electrode 28 and the piezoelectric/electrostrictive layer 26 are aligned, and only the forward end of the second electrode 30 is disposed at a position deviated toward the fixation section 22. The piezoelectric/electrostrictive device 10Ab shown in FIG. 3 is illustrative of the case in which mutually opposing end surfaces 36a, 36b are provided in the fixation section 22 in place of the movable section 20.

Alternatively, as in a piezoelectric/electrostrictive device 10Ac according to a third modified embodiment shown in FIG. 4, it is also preferable that the respective forward ends of the first electrode 28 and the piezoelectric/electrostrictive layer 26 are allowed to extend up to the side surface of the movable section 20, and the forward end of the second electrode 30 is located at an approximately central portion in the length direction (Z axis direction) of the thin plate section 16a, 16b.

In the embodiments described above, the piezoelectric /electrostrictive element 24a, 24b is constructed by the piezoelectric/electrostrictive layer 26 having the one-layered structure and the pair of electrodes 28, 30. Alternatively, it is also preferable that the

piezoelectric/electrostrictive element 24a, 24b is constructed in a stacked form composed of a plurality of units each comprising the piezoelectric/electrostrictive layer 26 and the pair of electrodes 28, 30.

5 For example, as in a piezoelectric/electrostrictive device 10Ad according to a fourth modified embodiment shown in FIG. 5, each of the piezoelectric/electrostrictive layer 26 and the pair of electrodes 28, 30 resides in a multilayered structure. The first electrodes 28 and the second electrodes 30 are alternately stacked with each other to provide the piezoelectric/electrostrictive element 24a, 24b which has a multiple stage structure at a portion (substantial driving portion 18) at which the first electrodes 28 and the second electrodes 30 are overlapped with each other with the piezoelectric/electrostrictive layer 26 interposed therebetween. FIG. 5 is illustrative of the following case. That is, the piezoelectric/electrostrictive layer 26 has the three-layered structure. The first electrodes 28 are formed in a separate manner respectively on the lower surface of the first layer (side surface of the thin plate section 16a, 16b) and on the upper surface of the second layer. The second electrodes 30 are formed in a separate manner respectively on the upper surface of the first layer and on the upper surface of the third layer. Further, terminals 32a, 32b are provided on respective ends of the first electrodes 28 respectively, and terminals 34a, 34b are provided on respective ends of the

second electrodes 30 respectively.

As in a piezoelectric/electrostrictive device 10Ae according to a fifth modified embodiment shown in FIG. 6, each of the piezoelectric/electrostrictive layer 26 and the pair of electrodes 28, 30 resides in a multilayered structure. The first electrode 28 and the second electrode 30 are alternately stacked with each other so that a substantially comb-shaped configuration is obtained in cross section to provide the piezoelectric/electrostrictive element 24a, 24b which has a multiple stage structure at a portion (substantial driving portion 18) at which the first electrode 28 and the second electrode 30 are overlapped with each other with the piezoelectric/electrostrictive layer 26 interposed therebetween. FIG. 6 is illustrative of the following case. That is, the piezoelectric/electrostrictive layer 26 has the three-layered structure. The first electrode 28 is formed in a comb-shaped configuration to be located on the lower surface of the first layer (side surface of the thin plate section 16a, 16b) and on the upper surface of the second layer. The second electrode 30 is formed in a comb-shaped configuration to be located on the upper surface of the first layer and on the upper surface of the third layer. In the case of this structure, each of the first electrode 28 and the second electrode 30 is continuous and common. Accordingly, it is possible to decrease the number of terminals 32, 34 as compared with the structure shown in FIG. 5. Therefore, it is possible to suppress the

increase in size which would be otherwise involved in the multilayered structure of the piezoelectric/electrostrictive element 24a, 24b.

Another example of the piezoelectric/electrostrictive device 10Ae according to the fifth embodiment is shown in FIG. 7. In this case, it is also preferable to form the piezoelectric/electrostrictive element 24a, 24b so that the forward end thereof stays on the thin plate section 16a, 16b. FIG. 7 is illustrative of the case in which the forward end of the piezoelectric/electrostrictive element 24a, 24b is located at a substantially central portion in the length direction of the thin plate section. This arrangement is advantageous in that the movable section 20 can be displaced to a great extent.

Alternatively, as in a piezoelectric/electrostrictive device 10Af according to a sixth modified embodiment shown in FIG. 8, it is also preferable that two piezoelectric/electrostrictive elements 24a1, 24b1 having the multiple stage structure are formed to extend over the fixation section 22 and the thin plate section 16a, 16b respectively, and another two piezoelectric/electrostrictive elements 24a2, 24b2 having the multiple stage structure are formed to extend over the movable section 20 and the thin plate section 16a, 16b respectively. In this arrangement, the movable section 20 can be displaced extremely greatly owing to the effect that the piezoelectric/electrostrictive element 24a, 24b has the multiple stage structure and the

effect that the number of points of action to displace the movable section 20 is increased. Further, the piezoelectric/electrostrictive device 10Af is excellent in high speed response performance, which is preferred.

5 Alternatively, as in a piezoelectric/electrostrictive device 10Ag according to a seventh modified embodiment shown in FIG. 9, it is also preferable that the piezoelectric /electrostrictive layer 26 has the two-layered structure to provide the piezoelectric/electrostrictive element 24a, 24b having the multiple stage structure which is formed such that the first electrode 28 is located on the lower surface of the first layer (side surface of the thin plate section 16a, 16b) and on the upper surface of the second layer, and the second electrode 30 is located on the upper surface of the first layer. In this embodiment, the space between the end surfaces 36a, 36b of the movable section 20 is filled with a member which is different from the movable section 20.

10
15
20 The multiple stage structure of the piezoelectric/electrostrictive element 24a, 24b as described above increases the force generated by the piezoelectric/electrostrictive element 24a, 24b, and thus it is possible to obtain the large displacement. Further, the rigidity of the piezoelectric/electrostrictive device 10A
25 itself is increased, and thus it is possible to realize the high resonance frequency. It is possible to achieve the high speed displacement action with ease.

When the number of stages is increased, it is possible to increase the driving force. However, the electric power consumption is also increased in accordance therewith. Therefore, when the device is practically produced and used, for example, it is preferable that the number of stages is appropriately determined depending on the way of use and the state of use. In the case of the piezoelectric /electrostrictive device 10A according to the first embodiment, even when the driving force is increased by providing the multiple stage structure of the piezoelectric/ electrostrictive element 24a, 24b, the width of the thin plate section 16a, 16b (distance in the Y axis direction) is basically unchanged. Therefore, the device is extremely preferred to make application, for example, to the actuator for the purpose of the ringing control and the positioning of the magnetic head for the hard disk to be used in an extremely narrow gap. Further, when the device is used as a sensor (for example, an acceleration sensor), the device provides the following advantage, because the electrostatic capacity is increased, and the generated electric charge is increased, owing to the multiple stage structure. That is, the level of the electric signal generated by the sensor is increased, and it is easy to perform the processing in a signal processing circuit to be connected to the downstream stage of the sensor.

The piezoelectric/electrostrictive element 24a, 24b is illustrative of the case of the so-called sandwich structure

in which the piezoelectric/electrostrictive layer 26 is interposed between the pair of electrodes 28, 30. Alternatively, as shown in FIG. 10, a pair of comb-shaped electrodes 28, 30 may be formed on the first principal surface of the piezoelectric/electrostrictive layer 26 formed on at least the side surface of the thin plate section 16a, 16b. Further alternatively, as shown in FIG. 11, a pair of comb-shaped electrodes 28, 30 are formed and embedded in the piezoelectric/electrostrictive layer 26 formed on at least the side surface of the thin plate section 16a, 16b.

The structure shown in FIG. 10 is advantageous in that it is possible to suppress the electric power consumption to be low. The structure shown in FIG. 11 makes it possible to effectively utilize the inverse piezoelectric effect in the direction of the electric field having large generated force and strain, which is advantageous to cause the large displacement.

Specifically, the piezoelectric/electrostrictive element 24a, 24b shown in FIG. 10 comprises the pair of electrodes 28, 30 having the comb-shaped structure formed on the first principal surface of the piezoelectric /electrostrictive layer 26. In this structure, the first electrode 28 and the second electrode 30 are mutually opposed to one another in an alternate manner with a gap 29 having a constant width interposed therebetween. FIG. 10 is illustrative of the case in which the pair of electrodes 28,

30 are formed on the first principal surface of the piezoelectric/electrostrictive layer 26. Alternatively, the pair of electrodes 28, 30 may be formed between the thin plate section 16a, 16b and the piezoelectric/electrostrictive layer 26. Further alternatively, the pair of comb-shaped electrodes 28, 30 may be formed on the first principal surface of the piezoelectric/electrostrictive layer 26 and between the thin plate section 16a, 16b and the piezoelectric/electrostrictive layer 26 respectively.

On the other hand, in the piezoelectric/electrostrictive element 24a, 24b shown in FIG. 11, the pair of electrodes 28, 30 having the comb-shaped structure are formed so that they are embedded in the piezoelectric/electrostrictive layer 26. In this structure, the first electrode 28 and the second electrode 30 are mutually opposed to one another in an alternate manner with a gap 29 having a constant width interposed therebetween.

The piezoelectric/electrostrictive elements 24a, 24b as shown in FIGS. 10 and 11 can be preferably used for the piezoelectric/electrostrictive device 10A according to the first embodiment as well. When the pair of comb-shaped electrodes 28, 30 are used as in the piezoelectric/electrostrictive elements 24a, 24b shown in FIGS. 10 and 11, the displacement of the piezoelectric/electrostrictive element 24a, 24b can be increased by decreasing the pitch D of the comb teeth of the respective electrodes 28, 30.

109672069-092800

5 The operation of the piezoelectric/electrostrictive device 10A according to the first embodiment will now be explained. At first, for example, when the two piezoelectric/electrostrictive elements 24a, 24b are in the natural state, namely when both of the piezoelectric /electrostrictive elements 24a, 24b do not make the displacement action, then the major axis m of the piezoelectric/electrostrictive device 10A (major axis of the fixation section) is substantially coincident with the central axis n of the movable section 20 as shown in FIG. 12.

15 Starting from this state, for example, a sine wave Wa, which has a predetermined bias electric potential Vb, is applied to the pair of electrodes 28, 30 of the first piezoelectric/electrostrictive element 24a as shown in a waveform figure shown in FIG. 13A, while a sine wave Wb, which has a phase different from that of the sine wave Wa by about 180°, is applied to the pair of electrodes 28, 30 of the second piezoelectric/electrostrictive element 24b as shown in FIG. 13B.

20

25 The piezoelectric/electrostrictive layer 26 of the first piezoelectric/electrostrictive element 24a makes the contraction displacement in the direction of the first principal surface at a stage at which, for example, a voltage having a maximum value is applied to the pair of electrodes 28, 30 of the first piezoelectric/electrostrictive element 24a. Accordingly, as

shown in FIG. 14, for example, the stress is generated for the first thin plate section 16a to bend the thin plate section 16a, for example, in the rightward direction as shown by the arrow A. Therefore, the first thin plate section 16a is bent in the rightward direction. At this time, a state is given, in which no voltage is applied to the pair of electrodes 28, 30 of the second piezoelectric /electrostrictive element 24b. Therefore, the second thin plate section 16b follows the bending of the first thin plate section 16a, and it is bent in the rightward direction. As a result, the movable section 20 is displaced, for example, in the rightward direction with respect to the major axis m of the piezoelectric /electrostrictive device 10A. The displacement amount is changed depending on the maximum value of the voltage applied to each of the piezoelectric/electrostrictive elements 24a, 24b. For example, the larger the maximum value is, the larger the displacement amount is.

Especially, when a material having high coercive electric field is applied as the constitutive material for the piezoelectric/electrostrictive layer 26, it is also preferable that the bias electric potential is adjusted so that the level of the minimum value is a slightly negative level as depicted by waveforms indicated by two-dot chain lines in FIGS. 13A and 13B. In this case, for example, the stress, which is in the same direction as the bending direction of the first thin plate section 16a, is generated

in the second thin plate section 16b by driving the piezoelectric /electrostrictive element (for example, the second piezoelectric/electrostrictive element 24b) to which the negative level is applied. Accordingly, it is possible to further increase the displacement amount of the movable section 20. In other words, when the waveforms indicated by the dashed lines in FIGS. 13A and 13B are used, the device is allowed to have such a function that the piezoelectric /electrostrictive element 24b or 24a, to which the negative level is applied, supports the piezoelectric /electrostrictive element 24a or 24b which principally makes the displacement action.

In the case of the piezoelectric/electrostrictive device 10Af shown in FIG. 8, the voltage (see the sine waveform Wa) shown in FIG. 13A is applied, for example, to the piezoelectric/electrostrictive element 24a1 and the piezoelectric/electrostrictive element 24b2 which are arranged on the diagonal line, and the voltage (see the sine waveform Wb) shown in FIG. 13B is applied to the other piezoelectric/electrostrictive element 24a2 and the other piezoelectric/electrostrictive element 24b1.

As described above, in the piezoelectric /electrostrictive device 10A according to the first embodiment, the minute displacement of the piezoelectric /electrostrictive element 24a, 24b is amplified into the large displacement action by utilizing the bending of the thin plate section 16a, 16b, and it is transmitted to the

movable section 20. Accordingly, it is possible to greatly displace the movable section 20 with respect to the major axis m of the piezoelectric/electrostrictive device 10A.

5 Especially, in the first embodiment, the movable section 20 is provided with the mutually opposing end surfaces 36a, 36b. In this arrangement, the gap 38 is provided between the mutually opposing end surfaces 36a, 36b, or the member 40, which is lighter than the constitutive member of the movable section 20, is allowed to intervene between the mutually opposing end surfaces 36a, 36b. Accordingly, it is possible to effectively realize the light weight of the movable section 20. Thus, it is possible to increase the resonance frequency without decreasing the displacement amount of the movable section 20.

10
15
20 The frequency herein indicates the frequency of the voltage waveform obtained when the movable section 20 is displaced rightwardly and leftwardly by alternately switching the voltage applied to the pair of electrodes 28, 30. The resonance frequency indicates the frequency at which the displacement action of the movable section 20 is maximum when the predetermined sine wave voltage is applied.

25 ~~In the piezoelectric/electrostrictive device 10A~~ according to the first embodiment, the hybrid structure is provided, in which the pair of thin plate sections 16a, 16b are made of metal, and the other components, i.e., the movable section 20 and the fixation section 22 are made of

Ins.
B19
cncl'd.

5 ~~ceramics. It is unnecessary that all of the parts are~~
formed with the piezoelectric /electrostrictive material
which is a fragile material having a relatively heavy
weight. Therefore, the device has the following advantages.
That is, the device has the high mechanical strength, and it
is excellent in handling performance, shock resistance, and
moisture resistance. Further, the operation of the device
is scarcely affected by harmful vibration (for example,
noise vibration and remaining vibration during high speed
operation).

10
15
Further, in this embodiment, when the gap 38 is formed
between the mutually opposing end surfaces 36a, 36b, the
part 20A of the movable section 20 including the first end
surface 36a and the another part 20B of the movable section
20 including the second end surface 36b are easily bent,
resulting in strong resistance to the deformation.
Accordingly, the piezoelectric/electrostrictive device 10A
is excellent in handling performance.

20
25
The surface area of the movable section 20 or the
fixation section 22 is increased owing to the presence of
the mutually opposing end surfaces 36a, 36b. Therefore, as
shown in FIG. 1, when the movable section 20 has the
mutually opposing end surfaces 36a, 36b, the attachment area
can be increased when another part is attached to the
movable section 20. Thus, it is possible to improve the
attachment performance for the part. It is now assumed that
the part is secured, for example, with an adhesive or the

like. In this case, the adhesive is fully distributed to the end surfaces 36a, 36b as well as to the first principal surface (attachment surface for the part) of the movable section 20. Therefore, it is possible to dissolve, for example, shortage of application of the adhesive. Thus, it is possible to reliably secure the part.

As an example of such an arrangement, FIG. 15 is illustrative of a case in which another piezoelectric /electrostrictive device according to the embodiment of the present invention (second piezoelectric/electrostrictive device 10A2) is secured to the movable section 20 of the piezoelectric/electrostrictive device according to the embodiment of the present invention (first piezoelectric /electrostrictive device 10A1).

The first piezoelectric/electrostrictive device 10A1 has its fixation section 22 which is secured to the surface of a base plate 122 by the aid of an adhesive 120. The fixation section 22 of the second piezoelectric/electrostrictive device 10A2 is secured to the movable section 20 of the first piezoelectric/electrostrictive device 10A1 by the aid of an adhesive 124. That is, in this arrangement, the two piezoelectric/electrostrictive devices 10A1, 10A2 are arranged in series. A member 126 having a light weight, which is different from the movable section 20, is allowed to intervene between the mutually opposing end surfaces 36a, 36b of the movable section 20 of the second piezoelectric/electrostrictive device 10A2.

In this case, the adhesive 124 for gluing the second piezoelectric/electrostrictive device 10A2 is fully distributed up to the space between the end surfaces 36a, 36b of the movable section 20 of the first piezoelectric /electrostrictive device 10A1. Accordingly, the second piezoelectric/electrostrictive device 10A2 is tightly secured to the first piezoelectric/electrostrictive device 10A1. When the piezoelectric/electrostrictive device 10A2 is glued as described above, the light weight member (adhesive 124 in this case), which is different from the movable section 20, is allowed to intervene between the end surfaces 36a, 36b simultaneously with the adhesion. Therefore, this arrangement is advantageous in that the production step can be simplified.

On the other hand, as shown in FIG. 3, when the fixation section 22 has the mutually opposing end surfaces 36a, 36b, it is possible to tightly fix the piezoelectric /electrostrictive device 10Ab according to the second modified embodiment to a predetermined fixation portion, in addition to the effect obtained when the movable section 20 has the mutually opposing end surfaces 36a, 36b as described above. Thus, it is possible to improve the reliability.

In the first embodiment, the portion (substantial driving portion 18), at which the pair of electrodes 28, 30 are overlapped with each other with the piezoelectric /electrostrictive layer 26 interposed therebetween, is continuously formed over the range from the part of the

fixation section 22 to the part of the thin plate section 16a, 16b. If the substantial driving portion 18 is formed to further extend over a part of the movable section 20, then it is feared that the displacement action of the movable section 20 is restricted by the substantial driving portion 18, and it is impossible to obtain the large displacement. However, in this embodiment, the substantial driving portion 18 is formed such that it does not range over the movable section 20. Therefore, it is possible to avoid the inconvenience of the restriction of the displacement action of the movable section 20, and it is possible to increase the displacement amount of the movable section 20.

On the other hand, when the piezoelectric/electrostrictive element 24a, 24b is formed on the part of the movable section 20, it is preferable that the substantial driving portion 18 is located over the range from the part of the movable section 20 to the part of the thin plate section 16a, 16b, because of the following reason. That is, if the substantial driving portion 18 is formed to extend up to a part of the fixation section 22, the displacement action of the movable section 20 is restricted as described above.

Next, explanation will be made for preferred illustrative constructions of the piezoelectric /electrostrictive device 10A according to the first embodiment.

At first, in order to ensure the displacement action of the movable section 20, it is preferable that the distance g, by which the substantial driving portion 18 of the piezoelectric/electrostrictive element 24a, 24b is overlapped with the fixation section 22 or the movable section 20, is not less than 1/2 of the thickness d of the thin plate section 16a, 16b.

The device is constructed such that the ratio a/b between the distance (distance in the X axis direction) a between the inner walls of the thin plate sections 16a, 16b and the width (distance in the Y axis direction) b of the thin plate section 16a, 16b is 0.5 to 20. The ratio a/b is preferably 1 to 15 and more preferably 1 to 10. The prescribed value of the ratio a/b is prescribed on the basis of the discovery that the displacement amount of the movable section 20 is increased to makes it possible to dominantly obtain the displacement in the X-Z plane.

On the other hand, it is desirable that the ratio e/a between the length (distance in the Z axis direction) e of the thin plate section 16a, 16b and the distance a between the inner walls of the thin plate sections 16a, 16b is preferably 0.5 to 10 and more preferably 0.5 to 5.

Further, it is preferable that the hole 12 is filled with a gel material, for example, silicon gel. Usually, the displacement action of the movable section 20 is restricted by the presence of such a filler material. However, in the first embodiment, it is intended to realize the light weight

brought about by the formation of the end surfaces 36a, 36b on the movable section 20 and increase the displacement amount of the movable section 20. Therefore, the restriction of the displacement action of the movable section 20 due to the filler material is counteracted. Accordingly, it is possible to realize the effect owing to the presence of the filler material, namely the realization of the high resonance frequency and the maintenance of the rigidity.

It is preferable that the length (distance in the Z axis direction) f of the movable section 20 is short, because of the following reason. That is, it is possible to realize the light weight and increase the resonance frequency by shortening the length. However, in order to ensure the rigidity of the movable section 20 in the X axis direction and obtain its reliable displacement, it is desirable that the ratio f/d with respect to the thickness d of the thin plate section 16a, 16b is not less than 2, and preferably not less than 5.

The actual size of each component is determined considering, for example, the joining area for attaching the part to the movable section 20, the joining area for attaching the fixation section 22 to another member, the joining area for attaching the electrode terminal or the like, and the strength, the durability, the necessary displacement amount, the resonance frequency, and the driving voltage of the entire piezoelectric/electrostrictive

device 10A.

Specifically, for example, the distance a between the inner walls of the thin plate sections 16a, 16b is preferably 100 μm to 2000 μm and more preferably 200 μm to 1600 μm . The width b of the thin plate section 16a, 16b is preferably 50 μm to 2000 μm and more preferably 100 μm to 500 μm . The thickness d of the thin plate section 16a, 16b is preferably 2 μm to 100 μm and more preferably 10 μm to 80 μm , while it satisfies $b > d$ in relation to the width b of the thin plate section 16a, 16b, in order to make it possible to effectively suppress the swaying displacement which is the displacement component in the Y axis direction.

The length e of the thin plate section 16a, 16b is preferably 200 μm to 3000 μm and more preferably 300 μm to 2000 μm . The length f of the movable section 20 is preferably 50 μm to 2000 μm and more preferably 100 μm to 1000 μm .

The arrangement as described above exhibits such an extremely excellent effect that the displacement in the Y axis direction does not exceeds 10 % with respect to the displacement in the X axis direction, while the device can be driven at a low voltage by appropriately making adjustment within the range of the size range and the actual size, and it is possible to suppress the displacement component in the Y axis direction to be not more than 5 %. In other words, the movable section 20 is displaced in one axis direction, i.e., substantially in the X axis direction.

Further, the high speed response is excellent, and it is possible to obtain the large displacement at a relatively low voltage.

5 In the piezoelectric/electrostrictive device 10A, the shape of the device is not the plate-shaped configuration (thickness is small in the direction perpendicular to the displacement direction) unlike conventional one. Each of the movable section 20 and the fixation section 22 has the approximately rectangular parallelepiped-shaped configuration. The pair of thin plate sections 16a, 16b are provided so that the side surface of the movable section 20 is continuous to the side surface of the fixation section 22. Therefore, it is possible to selectively increase the rigidity of piezoelectric/electrostrictive device 10A in the Y axis direction.

10 That is, in the piezoelectric/electrostrictive device 10A, it is possible to selectively generate only the operation of the movable section 20 in the plane (XZ plane). It is possible to suppress the operation of the movable section 20 in the YZ plane (operation in the so-called swaying direction).

20 Next, explanation will be made for the respective constitutive components of the piezoelectric/electrostrictive device 10A according to the first embodiment.

25 As described above, the movable section 20 is the portion which is operated on the basis of the driving amount

of the thin plate section 16a, 16b, and a variety of members are attached thereto depending on the purpose of use of the piezoelectric/electrostrictive device 10A. For example, when the piezoelectric/electrostrictive device 10A is used as a displacement element, a shield plate for an optical shutter or the like is attached thereto. Especially, when the piezoelectric/electrostrictive device 10A is used for the mechanism for positioning a magnetic head of a hard disk drive or for suppressing the ringing, a member required to be positioned is attached thereto, including, for example, the magnetic head, a slider provided with the magnetic head, and a suspension provided with the slider.

As described above, the fixation section 22 is the portion for supporting the thin plate sections 16a, 16b and the movable section 20. For example, in the case of the utilization to position the magnetic head of the hard disk drive, the entire piezoelectric/electrostrictive device 10A is fixed by supporting and securing the fixation section 22, for example, to a carriage arm attached to VCM (voice coil motor) or a fixation plate or a suspension attached to the carriage arm. As shown in FIG. 1, the terminals 32, 34 for driving the piezoelectric /electrostrictive elements 24a, 24b and other members are arranged on the fixation section 22 in some cases.

The material for constructing the movable section 20 and the fixation section 22 is not specifically limited provided that it has rigidity. However, it is possible to

preferably use ceramics to which the ceramic green sheet-
stacking method is applicable as described later on.
Specifically, the material includes, for example, materials
containing a major component of zirconia represented by
5 stabilized zirconia and partially stabilized zirconia,
alumina, magnesia, silicon nitride, aluminum nitride, and
titanium oxide, as well as materials containing a major
component of a mixture of them. However, in view of the
high mechanical strength and the high toughness, it is
preferable to use a material containing a major component of
zirconia, especially stabilized zirconia and a material
containing a major component of partially stabilized
zirconia. The metal material is not limited provided that
it has rigidity. However, the metal material includes, for
15 example, stainless steel, nickel, brass, cupronickel, and
bronze.

Those which are stabilized or partially stabilized as
follows are preferably used as stabilized zirconia or
partially stabilized zirconia as described above. That is,
20 the compound to be used for stabilizing or partially
stabilizing zirconia includes yttrium oxide, ytterbium
oxide, cerium oxide, calcium oxide, and magnesium oxide.
When at least one compound of them is added and contained,
zirconia is partially or fully stabilized. However, as for
25 the stabilization, the objective zirconia can be stabilized
not only by adding one type of the compound but also by
adding a combination of the compounds.

5 The amount of addition of each of the compounds is desirably as follows. That is, yttrium oxide or ytterbium oxide is added by 1 to 30 mole %, preferably 1.5 to 10 mole %. Cerium oxide is added by 6 to 50 mole %, preferably 8 to 20 mole %. Calcium oxide or magnesium oxide is added by 5 to 40 mole %, preferably 5 to 20 mole %. Especially, it is preferable to use yttrium oxide as a stabilizer. In this case, yttrium oxide is desirably added by 1.5 to 10 mole %, more preferably 2 to 4 mole %. For example, alumina, silica, or transition metal oxide may be added as an additive of sintering aid or the like in a range of 0.05 to 20 % by weight. However, when the sintering integration based on the film formation method is adopted as a technique for forming the piezoelectric/electrostrictive element 24a, 24b, it is also preferable to add, for example, alumina, magnesia, and transition metal oxide as an additive.

10
15
20
25 In order to obtain the mechanical strength and the stable crystal phase, it is desirable that the average crystal grain size of zirconia is 0.05 to 3 μm , preferably 0.05 to 1 μm . As described above, ceramics can be used for the thin plate section 16a, 16b in the same manner as in the movable section 20 and the fixation section 22. Preferably, it is advantageous to construct the thin plate sections 16a, 16b with a substantially identical material in view of the reliability of the joined portion and the strength of the piezoelectric/electrostrictive device 10A in order to reduce any complicated procedure of the production.

As described above, the thin plate section 16a, 16b is the portion which is driven in accordance with the displacement of the piezoelectric/electrostrictive element 24a, 24b. The thin plate section 16a, 16b is the thin plate-shaped member having flexibility, and it functions to amplify the expansion and contraction displacement of the piezoelectric/electrostrictive element 24a, 24b arranged on the surface as the bending displacement and transmit the displacement to the movable section 20. Therefore, it is enough that the shape or the material of the thin plate section 16a, 16b provides the flexibility with the mechanical strength of such a degree that it is not broken by the bending displacement. It is possible to make appropriate selection considering the response performance and the operability of the movable section 20.

It is preferable that the thickness d of the thin plate section 16a, 16b is preferably about $2\text{ }\mu\text{m}$ to $100\text{ }\mu\text{m}$. It is preferable that the combined thickness of the thin plate section 16a, 16b and the piezoelectric/electrostrictive element 24a, 24b is $7\text{ }\mu\text{m}$ to $500\text{ }\mu\text{m}$. It is preferable that the thickness of the electrode 28, 30 is 0.1 to $50\text{ }\mu\text{m}$, and the thickness of the piezoelectric/electrostrictive layer 26 is 3 to $300\text{ }\mu\text{m}$. The width b of the thin plate section 16a, 16b is preferably $50\text{ }\mu\text{m}$ to $2000\text{ }\mu\text{m}$.

On the other hand, as for the shape and the material for the thin plate section 16a, 16b, it is enough to use those having the flexibility and having the mechanical

strength of such a degree that no breakage occurs due to the bending displacement. Metal is preferably used. In this case, as described above, it is preferable to use a metal material which has the flexibility and which is capable of the bending displacement. Specifically, it is preferable to use a metal material which has a Young's modulus of not less than 100 GPa.

Preferably, it is desirable that the thin plate section 16a, 16b is made of an iron-based material such as various spring steel materials, maraging stainless steel materials, and stainless steel materials including, for example, austenite-based stainless steel materials such as SUS301, SUS304, AISI653, and SUH660, ferrite-based stainless steel materials such as SUS430 and SUS434, martensite-based stainless steel materials such as SUS410 and SUS630, and semiaustenite-based stainless steel materials such as SUS631 and AISI632. Alternatively, it is desirable that the thin plate section 16a, 16b is made of a non-ferrous material such as superelastic titanium alloy represented by titanium-nickel alloy, brass, cupronickel, aluminum, tungsten, molybdenum, beryllium copper, phosphor bronze, nickel, nickel-iron alloy, and titanium.

When ceramics is used for the thin plate section 16a, 16b in the same manner as the movable section 20a, 20b and the fixation section 22, it is preferable to use zirconia. Especially, a material containing a major component of stabilized zirconia and a material containing a major

component of partially stabilized zirconia are used most preferably, because of the large mechanical strength even in the case of the thin wall thickness, the high toughness, and the small reactivity with the piezoelectric/electrostrictive layer 26 and the electrode material.

The piezoelectric/electrostrictive element 24a, 24b has at least the piezoelectric/electrostrictive layer 26 and the pair of electrodes 28, 30 for applying the electric field to the piezoelectric/electrostrictive layer 26. It is possible to use, for example, piezoelectric/electrostrictive elements of the unimorph type and the bimorph type. However, those of the unimorph type combined with the thin plate section 16a, 16b are suitable for the piezoelectric /electrostrictive device 10A as described above, because they are excellent in stability of the generated displacement amount and they are advantageous to realize the light weight.

For example, as shown in FIG. 1, it is possible to preferably use, for example, the piezoelectric /electrostrictive element comprising the first electrode 28, the piezoelectric/electrostrictive layer 26, and the second electrode 30 which are stacked in the layered configuration. Additionally, it is also preferable to provide the multiple stage structure as shown in FIGS. 5 to 9. In this arrangement, the positional discrepancy of the film (electrode film) for constructing the electrode 28, 30, i.e., for example, the positional discrepancy of the

electrode 28 in the in-plane direction on the perpendicular projection plane disposed as every other layer is not more than 50 μm . This facts also holds for the electrode 30.

As shown in FIG. 1, the piezoelectric/electrostrictive element 24a, 24b is preferably formed on the outer surface side of the piezoelectric/electrostrictive device 10A in view of the fact that the thin plate sections 16a, 16b can be driven to a greater extent. However, the piezoelectric /electrostrictive element 24a, 24b may be formed on the inner surface side of the piezoelectric/electrostrictive device 10A, i.e., on the inner wall surface of the hole 12 depending on, for example, the form of use. Alternatively, the piezoelectric/electrostrictive elements 24a, 24b may be formed both on the outer surface side and on the inner surface side of the piezoelectric/electrostrictive device 10A.

Piezoelectric ceramics is preferably used for the piezoelectric/electrostrictive layer 26. However, it is also possible to use electrostrictive ceramics, ferroelectric ceramics, or anti-ferroelectric ceramics. However, when the piezoelectric/electrostrictive device 10A is used, for example, to position the magnetic head of the hard disk drive, it is important to provide the linearity concerning the displacement amount of the movable section 20 and the driving voltage or the output voltage. Therefore, it is preferable to use a material having small strain hysteresis. It is preferable to use a material having a

coercive electric field of not more than 10 kV/mm.

Specified materials include ceramics containing, for example, lead zirconate, lead titanate, lead magnesium niobate, lead nickel niobate, lead zinc niobate, lead manganese niobate, lead antimony stannate, lead manganese tungstate, lead cobalt niobate, barium titanate, sodium bismuth titanate, potassium sodium niobate, and strontium bismuth tantalate singly or in mixture.

Especially, a material containing a major component of lead zirconate, lead titanate, and lead magnesium niobate, or a material containing a major component of sodium bismuth titanate is preferably used, in order to obtain the product having a stable composition with a high electromechanical coupling coefficient and a piezoelectric constant and with small reactivity with the thin plate sections 16a, 16b (ceramics) when the thin plate section 16a, 16b is made of ceramics, and the piezoelectric /electrostrictive layer 26 is sintered in an integrated manner.

It is also preferable to use ceramics obtained by adding, to the material described above, for example, oxides of lanthanum, calcium, strontium, molybdenum, tungsten, barium, niobium, zinc, nickel, manganese, cerium, cadmium, chromium, cobalt, antimony, iron, yttrium, tantalum, lithium, bismuth, and stannum, or compounds each containing at least one component to be finally formed into oxide, singly or in mixture.

For example, when lanthanum and/or strontium is

contained in the major components of lead zirconate, lead titanate, and lead magnesium niobate, an advantage is obtained in some cases, for example, in such a way that the coercive electric field and the piezoelectric characteristic can be adjusted.

It is desirable to avoid the addition of a material such as silica which tends to form glass, because of the following reason. That is, the material such as silica tends to react with the piezoelectric/electrostrictive material during the heat treatment for the piezoelectric /electrostrictive layer. As a result, the composition is varied, and the piezoelectric characteristic is deteriorated.

On the other hand, it is preferable that the piezoelectric/electrostrictive element 24a, 24b and the pair of electrodes 28, 30 are made of metal which is solid at room temperature and which is excellent in conductivity. For example, it is possible to use metal simple substance or alloy of, for example, aluminum, titanium, chromium, iron, cobalt, nickel, copper, zinc, niobium, molybdenum, ruthenium, palladium, rhodium, silver, stannum, tantalum, tungsten, iridium, platinum, gold, and lead. It is also preferable to use a cermet material obtained by dispersing, in the metal described above, ceramics of the same material as that of the piezoelectric/electrostrictive layer 26 or the material different from that of the piezoelectric/electrostrictive layer 26.

5 The material for the electrodes 28, 30 of the
piezoelectric/electrostrictive element 24a, 24b is selected
and determined depending on the method for forming the
piezoelectric/electrostrictive layer 26. For example, when
the piezoelectric/electrostrictive layer 26 is formed by
sintering on the first electrode 28 after the first
electrode 28 is formed on the thin plate section 16a, 16b,
it is necessary for the first electrode 28 to use high
melting point metal such as platinum, palladium, platinum-
palladium alloy, and silver-palladium alloy which does not
change at the sintering temperature for the piezoelectric
/electrostrictive layer 26. However, the electrode
formation can be performed at a low temperature for the
second electrode 30 which is formed on the piezoelectric
/electrostrictive layer 26 when located at the outermost
layer after forming the piezoelectric /electrostrictive
layer 26. Therefore, it is possible for the second
electrode 30 to use low melting point metal such as
aluminum, gold, and silver.

20
Ins.
B20
25
~~When the stacked type piezoelectric/electrostrictive~~
element 24 is stuck to the thin plate section 16a, 16b by
the aid of the adhesive 202, it is preferable that the
piezoelectric/electrostrictive layer 26 and the electrodes
28, 30 (electrode films) are stacked and integrated into one
unit in a multilayered configuration, and then they are
collectively sintered. In this case, high melting point
~~metal such as platinum, palladium, and alloy thereof is used~~

Ins.
B20
Cmcl'd.

~~for the electrodes 28, 30. It is preferable that the electrode 28, 30 is made of cermet as a mixture of the high melting point metal and the piezoelectric/electrostrictive material or another ceramics.~~

5 The thickness of the electrode 28, 30 also serves as a factor to considerably decrease the displacement of the piezoelectric/electrostrictive element 24a, 24b. Therefore, it is preferable, especially for the electrode formed after the sintering of the piezoelectric/electrostrictive layer 26, to use organic metal paste capable of obtaining a dense and thinner film after the sintering, for example, a material such as gold resinate paste, platinum resinate paste, and silver resinate paste.

10
15 Next, explanation will be made with reference to FIGS. 16A to 23 for several methods for producing the piezoelectric/electrostrictive device 10A according to the first embodiment.

20 In the piezoelectric/electrostrictive device 10A according to the first embodiment, the thin plate section 16a, 16b is made of metal, and the constitutive material for each of the movable section 20 and the fixation section 22 is ceramics. Therefore, it is preferable that the constitutive elements of the piezoelectric/electrostrictive device 10A concerning the fixation section 22 and the
25 movable section 20, except for the thin plate sections 16a, 16b and the piezoelectric /electrostrictive elements 24a, 24b, are produced by using the ceramic green sheet-stacking

method. On the other hand, it is preferable that the piezoelectric/electrostrictive elements 24a, 24b as well as the respective terminals 32, 34 are produced by using the film formation method, for example, for the thin film and the thick film.

The thin plate sections 16a, 16b are preferably secured to the side surfaces of the movable section 20 and the fixation section 22 by the aid of the adhesive 200. The piezoelectric/electrostrictive element 24a, 24b is preferably secured onto the thin plate section 16a, 16b by the aid of the adhesive 202.

According to the ceramic green sheet-stacking method in which the movable section 20 and the fixation section 22 of the piezoelectric/electrostrictive device 10A can be formed in an integrated manner, the time-dependent change of state scarcely occurs at the joined portions of the respective members. Therefore, this method provides the high reliability of the joined portion, and it is advantageous to ensure the rigidity.

In the piezoelectric/electrostrictive device 10A according to the first embodiment, the boundary portion between the thin plate section 16a, 16b and the fixation section 22 and the boundary portion between the thin plate section 16a, 16b and the movable section 20 function as supporting points for expressing the displacement. Therefore, the reliability of each of the boundary portions is an important point which dominates the characteristic of

the piezoelectric/electrostrictive device 10A.

The production methods described below are excellent in reproducibility and formability. Therefore, it is possible to obtain the piezoelectric/electrostrictive device having a predetermined shape within a short period of time with good reproducibility.

A first production method for the piezoelectric /electrostrictive device 10A according to the first embodiment will be specifically explained below. The following definitions are now made. The stack, which is obtained by stacking the ceramic green sheets, is defined to be the ceramic green stack 158 (see, for example, FIG. 16B). The integrated matter, which is obtained by sintering the ceramic green stack 158, is defined to be the ceramic stack 160 (see, for example, FIG. 17A). The stuck or glued matter comprising the ceramic stack 160 and the metal plate is defined to be the hybrid stack 162 (see FIG. 18). The integrated matter comprising the movable section 20, the thin plate sections 16a, 16b, and the fixation section 22, which is obtained by cutting off unnecessary portions from the hybrid stack 162, is defined to be the substrate 14D (see FIG. 19).

In the first production method, the hybrid stack 162 is finally cut into chip units to produce a large number of piezoelectric/electrostrictive devices 10A. However, in order to simplify the explanation, description will be made principally for the case in which one individual of

piezoelectric/electrostrictive device 10A is produced.

At first, for example, a binder, a solvent, a dispersing agent, and a plasticizer are added and mixed with a ceramic powder such as zirconia to prepare a slurry. The slurry is subjected to a defoaming treatment, and then a ceramic green sheet having a predetermined thickness is prepared in accordance with, for example, the reverse roll coater method and the doctor blade method.

Subsequently, the ceramic green sheet is processed into those having various shapes as shown in FIG. 16A in accordance with, for example, the punching out based on the use of the mold and the laser machining to prepare a plurality of ceramic green sheets for forming the substrate. Specifically, a plurality (for example, four) of ceramic green sheets 50A to 50D each of which is formed with a window 54 for forming at least the hole 12 thereafter, and a ceramic green sheet 102 which is continuously formed with a window 54 for forming the hole 12 thereafter and a window 100 for forming the movable section 20 having the mutually opposing end surfaces 36a, 36b are prepared.

After that, as shown in FIG. 16B, the ceramic green sheets 50A to 50D, 102 are stacked and secured under pressure to form a ceramic green stack 158. The stacking is performed while the ceramic green sheet 102 is positioned at the center. After that, the ceramic green stack 158 is sintered to obtain a ceramic stack 160 as shown in FIG. 17A. At this stage, the ceramic stack 160 is formed such that the

hole 130 is formed by the windows 54, 100.

Subsequently, as shown in FIG. 17B, the piezoelectric /electrostrictive elements 24a, 24b, which are constructed as separate members, are respectively glued with an epoxy adhesive 202 to the surfaces of metal plates 152A, 152B to serve as the thin plate sections.

Subsequently, the metal plates 152A, 152B are glued to the ceramic stack 160 with an epoxy adhesive 200 so that the ceramic stack 160 is interposed between the metal plates 152A, 152B and the hole 130 is closed thereby to provide a hybrid stack 162 (see FIG. 18).

Subsequently, as shown in FIG. 18, the hybrid stack 162, which is formed with the piezoelectric/electrostrictive elements 24a, 24b, is cut along cutting lines C1, C2, C5 to thereby cut off side portions and forward end portions of the hybrid stack 162. As a result of the cutoff, as shown in FIG. 19, the piezoelectric/electrostrictive device 10A according to the first embodiment is obtained, in which the piezoelectric/electrostrictive elements 24a, 24b are formed on the thin plate sections constituted by the metal plates, of the substrate 14D, and the movable section 20 having the mutually opposing end surfaces 36a, 36b is formed.

On the other hand, in the second production method, at first, as shown in FIG. 20A, a plurality (for example, four) of ceramic green sheets 50A to 50D each of which is formed with a window 54 for forming at least the hole 12 thereafter, and a ceramic green sheet 102 which is

continuously formed with a window 54 for forming the hole 12 thereafter and a window 100 for forming the movable section 20 having the mutually opposing end surfaces 36a, 36b are prepared.

5 After that, as shown in FIG. 20B, the ceramic green sheets 50A to 50D, 102 are stacked and secured under pressure to form a ceramic green stack 158. After that, the ceramic green stack 158 is sintered to obtain a ceramic stack 160 as shown in FIG. 21A. At this stage, the ceramic stack 160 is formed such that the hole 130 is formed by the windows 54, 100.

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995
1000
1005
1010
1015
1020
1025
1030
1035
1040
1045
1050
1055
1060
1065
1070
1075
1080
1085
1090
1095
1100
1105
1110
1115
1120
1125
1130
1135
1140
1145
1150
1155
1160
1165
1170
1175
1180
1185
1190
1195
1200
1205
1210
1215
1220
1225
1230
1235
1240
1245
1250
1255
1260
1265
1270
1275
1280
1285
1290
1295
1300
1305
1310
1315
1320
1325
1330
1335
1340
1345
1350
1355
1360
1365
1370
1375
1380
1385
1390
1395
1400
1405
1410
1415
1420
1425
1430
1435
1440
1445
1450
1455
1460
1465
1470
1475
1480
1485
1490
1495
1500
1505
1510
1515
1520
1525
1530
1535
1540
1545
1550
1555
1560
1565
1570
1575
1580
1585
1590
1595
1600
1605
1610
1615
1620
1625
1630
1635
1640
1645
1650
1655
1660
1665
1670
1675
1680
1685
1690
1695
1700
1705
1710
1715
1720
1725
1730
1735
1740
1745
1750
1755
1760
1765
1770
1775
1780
1785
1790
1795
1800
1805
1810
1815
1820
1825
1830
1835
1840
1845
1850
1855
1860
1865
1870
1875
1880
1885
1890
1895
1900
1905
1910
1915
1920
1925
1930
1935
1940
1945
1950
1955
1960
1965
1970
1975
1980
1985
1990
1995
2000
2005
2010
2015
2020
2025
2030
2035
2040
2045
2050
2055
2060
2065
2070
2075
2080
2085
2090
2095
2100
2105
2110
2115
2120
2125
2130
2135
2140
2145
2150
2155
2160
2165
2170
2175
2180
2185
2190
2195
2200
2205
2210
2215
2220
2225
2230
2235
2240
2245
2250
2255
2260
2265
2270
2275
2280
2285
2290
2295
2300
2305
2310
2315
2320
2325
2330
2335
2340
2345
2350
2355
2360
2365
2370
2375
2380
2385
2390
2395
2400
2405
2410
2415
2420
2425
2430
2435
2440
2445
2450
2455
2460
2465
2470
2475
2480
2485
2490
2495
2500
2505
2510
2515
2520
2525
2530
2535
2540
2545
2550
2555
2560
2565
2570
2575
2580
2585
2590
2595
2600
2605
2610
2615
2620
2625
2630
2635
2640
2645
2650
2655
2660
2665
2670
2675
2680
2685
2690
2695
2700
2705
2710
2715
2720
2725
2730
2735
2740
2745
2750
2755
2760
2765
2770
2775
2780
2785
2790
2795
2800
2805
2810
2815
2820
2825
2830
2835
2840
2845
2850
2855
2860
2865
2870
2875
2880
2885
2890
2895
2900
2905
2910
2915
2920
2925
2930
2935
2940
2945
2950
2955
2960
2965
2970
2975
2980
2985
2990
2995
3000
3005
3010
3015
3020
3025
3030
3035
3040
3045
3050
3055
3060
3065
3070
3075
3080
3085
3090
3095
3100
3105
3110
3115
3120
3125
3130
3135
3140
3145
3150
3155
3160
3165
3170
3175
3180
3185
3190
3195
3200
3205
3210
3215
3220
3225
3230
3235
3240
3245
3250
3255
3260
3265
3270
3275
3280
3285
3290
3295
3300
3305
3310
3315
3320
3325
3330
3335
3340
3345
3350
3355
3360
3365
3370
3375
3380
3385
3390
3395
3400
3405
3410
3415
3420
3425
3430
3435
3440
3445
3450
3455
3460
3465
3470
3475
3480
3485
3490
3495
3500
3505
3510
3515
3520
3525
3530
3535
3540
3545
3550
3555
3560
3565
3570
3575
3580
3585
3590
3595
3600
3605
3610
3615
3620
3625
3630
3635
3640
3645
3650
3655
3660
3665
3670
3675
3680
3685
3690
3695
3700
3705
3710
3715
3720
3725
3730
3735
3740
3745
3750
3755
3760
3765
3770
3775
3780
3785
3790
3795
3800
3805
3810
3815
3820
3825
3830
3835
3840
3845
3850
3855
3860
3865
3870
3875
3880
3885
3890
3895
3900
3905
3910
3915
3920
3925
3930
3935
3940
3945
3950
3955
3960
3965
3970
3975
3980
3985
3990
3995
4000
4005
4010
4015
4020
4025
4030
4035
4040
4045
4050
4055
4060
4065
4070
4075
4080
4085
4090
4095
4100
4105
4110
4115
4120
4125
4130
4135
4140
4145
4150
4155
4160
4165
4170
4175
4180
4185
4190
4195
4200
4205
4210
4215
4220
4225
4230
4235
4240
4245
4250
4255
4260
4265
4270
4275
4280
4285
4290
4295
4300
4305
4310
4315
4320
4325
4330
4335
4340
4345
4350
4355
4360
4365
4370
4375
4380
4385
4390
4395
4400
4405
4410
4415
4420
4425
4430
4435
4440
4445
4450
4455
4460
4465
4470
4475
4480
4485
4490
4495
4500
4505
4510
4515
4520
4525
4530
4535
4540
4545
4550
4555
4560
4565
4570
4575
4580
4585
4590
4595
4600
4605
4610
4615
4620
4625
4630
4635
4640
4645
4650
4655
4660
4665
4670
4675
4680
4685
4690
4695
4700
4705
4710
4715
4720
4725
4730
4735
4740
4745
4750
4755
4760
4765
4770
4775
4780
4785
4790
4795
4800
4805
4810
4815
4820
4825
4830
4835
4840
4845
4850
4855
4860
4865
4870
4875
4880
4885
4890
4895
4900
4905
4910
4915
4920
4925
4930
4935
4940
4945
4950
4955
4960
4965
4970
4975
4980
4985
4990
4995
5000
5005
5010
5015
5020
5025
5030
5035
5040
5045
5050
5055
5060
5065
5070
5075
5080
5085
5090
5095
5100
5105
5110
5115
5120
5125
5130
5135
5140
5145
5150
5155
5160
5165
5170
5175
5180
5185
5190
5195
5200
5205
5210
5215
5220
5225
5230
5235
5240
5245
5250
5255
5260
5265
5270
5275
5280
5285
5290
5295
5300
5305
5310
5315
5320
5325
5330
5335
5340
5345
5350
5355
5360
5365
5370
5375
5380
5385
5390
5395
5400
5405
5410
5415
5420
5425
5430
5435
5440
5445
5450
5455
5460
5465
5470
5475
5480
5485
5490
5495
5500
5505
5510
5515
5520
5525
5530
5535
5540
5545
5550
5555
5560
5565
5570
5575
5580
5585
5590
5595
5600
5605
5610
5615
5620
5625
5630
5635
5640
5645
5650
5655
5660
5665
5670
5675
5680
5685
5690
5695
5700
5705
5710
5715
5720
5725
5730
5735
5740
5745
5750
5755
5760
5765
5770
5775
5780
5785
5790
5795
5800
5805
5810
5815
5820
5825
5830
5835
5840
5845
5850
5855
5860
5865
5870
5875
5880
5885
5890
5895
5900
5905
5910
5915
5920
5925
5930
5935
5940
5945
5950
5955
5960
5965
5970
5975
5980
5985
5990
5995
6000
6005
6010
6015
6020
6025
6030
6035
6040
6045
6050
6055
6060
6065
6070
6075
6080
6085
6090
6095
6100
6105
6110
6115
6120
6125
6130
6135
6140
6145
6150
6155
6160
6165
6170
6175
6180
6185
6190
6195
6200
6205
6210
6215
6220
6225
6230
6235
6240
6245
6250
6255
6260
6265
6270
6275
6280
6285
6290
6295
6300
6305
6310
6315
6320
6325
6330
6335
6340
6345
6350
6355
6360
6365
6370
6375
6380
6385
6390
6395
6400
6405
6410
6415
6420
6425
6430
6435
6440
6445
6450
6455
6460
6465
6470
6475
6480
6485
6490
6495
6500
6505
6510
6515
6520
6525
6530
6535
6540
6545
6550
6555
6560
6565
6570
6575
6580
6585
6590
6595
6600
6605
6610
6615
6620
6625
6630
6635
6640
6645
6650
6655
6660
6665
6670
6675
6680
6685
6690
6695
6700
6705
6710
6715
6720
6725
6730
6735
6740
6745
6750
6755
6760
6765
6770
6775
6780
6785
6790
6795
6800
6805
6810
6815
6820
6825
6830
6835
6840
6845
6850
6855
6860
6865
6870
6875
6880
6885
6890
6895
6900
6905
6910
6915
6920
6925
6930
6935
6940
6945
6950
6955
6960
6965
6970
6975
6980
6985
6990
6995
7000
7005
7010
7015
7020
7025
7030
7035
7040
7045
7050
7055
7060
7065
7070
7075
7080
7085
7090
7095
7100
7105
7110
7115
7120
7125
7130
7135
7140
7145
7150
7155
7160
7165
7170
7175
7180
7185
7190
7195
7200
7205
7210
7215
7220
7225
7230
7235
7240
7245
7250
7255
7260
7265
7270
7275
7280
7285
7290
7295
7300
7305
7310
7315
7320
7325
7330
7335
7340
7345
7350
7355
7360
7365
7370
7375
7380
7385
7390
7395
7400
7405
7410
7415
7420
7425
7430
7435
7440
7445
7450
7455
7460
7465
7470
7475
7480
7485
7490
7495
7500
7505
7510
7515
7520
7525
7530
7535
7540
7545
7550
7555
7560
7565
7570
7575
7580
7585
7590
7595
7600
7605
7610
7615
7620
7625
7630
7635
7640
7645
7650
7655
7660
7665
7670
7675
7680
7685
7690
7695
7700
7705
7710
7715
7720
7725
7730
7735
7740
7745
7750
7755
7760
7765
7770
7775
7780
7785
7790
7795
7800
7805
7810
7815
7820
7825
7830
7835
7840
7845
7850
7855
7860
7865
7870
7875
7880
7885
7890
7895
7900
7905
7910
7915
7920
7925
7930
7935
7940
7945
7950
7955
7960
7965
7970
7975
7980
7985
7990
7995
8000
8005
8010
8015
8020
8025
8030
8035
8040
8045
8050
8055
8060
8065
8070
8075
8080
8085
8090
8095
8100
8105
8110
8115
8120
8125
8130
8135
8140
8145
8150
8155
8160
8165
8170
8175
8180
8185
8190
8195
8200
8205
8210
8215
8220
8225
8230
8235
8240
8245
8250
8255
8260
8265
8270
8275
8280
8285
8290
8295
8300
8305
8310
8315
8320
8325
8330
8335
8340
8345
8350
8355
8360
8365
8370
8375
8380
8385
8390
8395
8400
8405
8410
8415
8420
8425
8430
8435
8440
8445
8450
8455
8460
8465
8470
8475
8480
8485
8490
8495
8500
8505
8510
8515
8520
8525
8530
8535
8540
8545
8550
8555
8560
8565
8570
8575
8580
8585
8590
8595
8600
8605
8610
8615
8620
8625
8630
8635
8640
8645
8650
8655
8660
8665
8670
8675
8680
8685
8690
8695
8700
8705
8710
8715
8720
8725
8730
8735
8740
8745
8750
8755
8760
8765
8770
8775
8780
8785
8790
8795
8800
8805
8810
8815
8820
8825
8830
8835
8840
8845
8850
8855
8860
8865
8870
8875
8880
8885
8890
8895
8900
8905
8910
8915
8920
8925
8930
8935
8940
8945
8950
8955
8960
8965
8970
8975
8980
8985
8990
8995
9000
9005
9010
9015
9020
9025
9030
9035
9040
9045
9050
9055
9060
9065
9070
9075
9080
9085
9090
9095
9100
9105
9110
9115
9120
9125
9130
9135
9140
9145
9150
9155
9160
9165
9170
9175
9180
9185
9190
9195
9200
9205
9210
9215
9220
9225
9230
9235
9240
9245
9250
9255
9260
9265
9270
9275
9280
9285
9290
9295
9300
9305
9310
9315
9320
9325
9330
9335
9340
9345
9350
9355
9360
9365
9370
9375
9380
9385
9390
9395
9400
9405
9410
9415
9420
9425
9430
9435
9440
9445
9450
9455
9460
9465
9470
9475
9480
9485
9490
9495
9500
9505
9510
9515
9520
9525
9530
9535
9540
9545
9550
9555
9560
9565
9570
9575
9580
9585
9590
9595
9600
9605
9610
9615
9620
9625
9630
9635
9640
9645
9650
9655
9660
9665
9670
9675
9680
9685
9690
9695
9700
9705
9710
9715
9720
9725
9730
9735
9740
9745
9750
9755
9760
9765
9770
9775
9780
9785
9790
9795
9800
9805
9810
9815
9820
9825
9830
9835
9840
9845
9850
9855
9860
9865
9870
9875
9880
9885
9890
9895
9900
9905
9910
9915
9920
9925
9930
9935
9940
9945
9950
9955
9960
9965
9970
9975
9980
9985
9990
9995
10000
10005
10010
10015
10020
10025
10030
10035
10040
10045
10050
10055
10060
10065
10070
10075
10080
10085
10090
10095
10100
10105
10110
10115
10120
10125
10130
10135
10140
10145
10150
10155
10160
10165
10170
10175
10180
10185
10190
10195
10200
10205
10210
10215
10220
10225
10230
10235
10240
10245

organic resin such as acrylic.

Subsequently, as shown in FIG. 21B, the piezoelectric /electrostrictive elements 24a, 24b, which are constructed as separate members, are glued with the epoxy adhesive 202 to the surfaces of the metal plates 152A, 152B of the hybrid stack 162. The separate members of the piezoelectric /electrostrictive elements 24a, 24b can be formed, for example, in accordance with the ceramic green sheet-stacking method.

Subsequently, as shown in FIG. 22, the hybrid stack 162, which is formed with the piezoelectric/electrostrictive elements 24a, 24b, is cut along cutting lines C1, C2, C5 to thereby cut off side portions and forward end portions of the hybrid stack 162. As a result of the cutoff, as shown in FIG. 23, the piezoelectric/electrostrictive device 10A according to the first embodiment is obtained, in which the piezoelectric /electrostrictive elements 24a, 24b are formed on the thin plate sections constituted by the metal plates, of the substrate 14D, and the movable section 20 having the mutually opposing end surfaces 36a, 36b is formed.

When all of the substrate section is made of metal, for example, the portions corresponding to the ceramic stack 160 shown in FIG. 17A are formed by means of molding. Further, bulk-shaped members may be formed in accordance with the method of grinding machining, wire electric discharge machining, mold stamping, or chemical etching, or thin metal materials may be stacked to form the substrate section in

accordance with the cladding method.

Next, a piezoelectric/electrostrictive device 10B according to the second embodiment will be explained with reference to FIGS. 24 to 52.

5 As shown in FIG. 24, the piezoelectric/electrostrictive device 10B according to the second embodiment comprises a pair of mutually opposing thin plate sections 16a, 16b, and a fixation section 22 for supporting the thin plate sections 16a, 16b. A stacked type piezoelectric/electrostrictive element 24 is arranged on one thin plate section 16a of the pair of thin plate sections 16a, 16b. In FIGS. 24 and 25, the stacked type piezoelectric/electrostrictive element 24 is illustrated in a simplified manner, because its structure is complicated. Details are shown in magnified views of FIGS. 26 to 29.

10 The fixation section 22 is secured, for example, by the aid of an adhesive 200 between the respective rearward ends of the pair of thin plate sections 16a, 16b. The forward ends of the pair of thin plate sections 16a, 16b are open ends.

15 As shown in FIG. 25, for example, the movable section 20 or various parts and members are secured, for example, by the aid of the adhesive 200 between the respective forward ends of the pair of thin plate sections 16a, 16b. The example shown in FIG. 25 is illustrative of the case in which the movable section 20, which is constructed by the same member as that of the fixation section 22, is secured

by the aid of the adhesive 200 between the respective forward ends of the pair of thin plate sections 16a, 16b.

Each of the pair of thin plate sections 16a, 16b is made of metal. The fixation section 22 and the movable section 20 are made of ceramics or metal. Especially, in the examples shown in FIGS. 24 and 25, the thickness of the first thin plate section 16a on which the stacked type piezoelectric/electrostrictive element 24 is formed, of the pair of thin plate sections 16a, 16b is larger than the thickness of the second thin plate section 16b.

10
INS. B22

~~The stacked type piezoelectric/electrostrictive element 24 is stuck to the thin plate section 16b by the aid of an adhesive 202 such as organic resin, glass, brazing, soldering, and eutectic bonding. That is, the stacked type piezoelectric/electrostrictive element 24 is secured by the adhesive 202 to the thin plate section 16a made of metal to thereby construct an actuator section 204 which is the driving source of the piezoelectric/electrostrictive device~~
10B.

In the piezoelectric/electrostrictive device 10B, the forward end (portion to which the movable section 20 is attached) of the thin plate section 16a (16a and 16b in the example shown in FIG. 25) is displaced in accordance with the driving of the actuator section 204. Alternatively, the displacement of the forward end of the thin plate section 16a is electrically detected by the aid of the actuator section (transducer section in the case of the use as a

sensor) 204. In this case, the device is utilized as a sensor.

As shown in FIG. 26, for example, the stacked type piezoelectric/electrostrictive element 24 is constructed as follows. That is, each of the piezoelectric /electrostrictive layer 26 and the pair of electrodes 28, 30 has the multilayered structure, and the first electrodes 28 and the second electrodes 30 are alternately stacked respectively to give the multiple stage structure at the portion at which the first electrodes 28 and the second electrodes 30 are overlapped with each other with the piezoelectric /electrostrictive layer 26 intervening therebetween.

In FIG. 26, each of the piezoelectric/electrostrictive layer 26 and the pair of electrodes 28, 30 has the multilayered structure. The first electrode 28 and the second electrode 30 are alternately stacked with each other to give the substantially comb-shaped configuration. The multiple stage structure is formed at the portion at which the first electrode 28 and the second electrode 30 are overlapped with each other with the piezoelectric /electrostrictive layer 26 interposed therebetween.

Specifically, the stacked type piezoelectric/electrostrictive element 24 has the approximately rectangular parallelepiped-shaped configuration, comprising a plurality of piezoelectric/electrostrictive layers 26 and a plurality of electrode films 28, 30. The electrode films 28, 30, which

contact with the upper and lower surfaces of each of the piezoelectric/electrostrictive layers 26, are alternately led to opposite end surfaces 208, 209 respectively. End surface electrodes 28c, 30c, which electrically connect the respective electrode films 28, 30 alternately led to the opposite end surfaces 208, 209, are electrically connected to terminals 28b, 30b which are formed on the surface of the outermost layer of the piezoelectric/electrostrictive layer 26 and which are arranged while being separated from each other by a predetermined distance Dk.

It is preferable that the predetermined distance Dk between the terminals 28b, 30b is not less than 20 μm . Further, the material of the electrode films 28, 30 to make contact with the upper and lower surfaces of the piezoelectric/electrostrictive layer may be different from the material of the end surface electrodes 28c, 30c. Further, at least one of the terminals (terminal 28b in the example shown in FIG. 26) and the end surface electrode 28c corresponding to the terminal 28b may be electrically connected with a thin film electrode film (outer surface electrode) 28d which is thinner than the terminal 28b and the end surface electrode 28c.

The surface electrode film 28d, the end surface electrodes 28c, 30c, and the terminals 28b, 30b, which are formed before sintering the piezoelectric/electrostrictive layer 26, may be thin, and they may have low heat resistance, as compared with the electrode layers 28, 30

which are formed before sintering the piezoelectric/electrostrictive layer 26 or which are sintered simultaneously.

FIG. 26 is illustrative of the following case. That is, the piezoelectric/electrostrictive layer 26 has the five-layered structure. The first electrodes 28 are formed in the comb-shaped configuration so that they are disposed on the upper surface of the first layer, the upper surface of the third layer, and the upper surface of the fifth layer. The second electrodes 30 are formed in the comb-shaped configuration so that they are disposed on the upper surface of the second layer and the upper surface of the fourth layer.

FIG. 28 is illustrative of the following case. That is, the piezoelectric/electrostrictive layer 26 has the five-layered structure as well. The first electrodes 28 are formed in the comb-shaped configuration so that they are disposed on the upper surface of the first layer, the upper surface of the third layer, and the upper surface of the fifth layer. The second electrodes 30 are formed in the comb-shaped configuration so that they are disposed on the lower surface of the first layer, the upper surface of the second layer, and the upper surface of the fourth layer.

In the case of the structures described above, it is possible to suppress the increase in number of terminals by connecting the mutual first electrodes 28 and the mutual second electrodes 30 with each other to be common.

Therefore, it is possible to suppress the increase in size, which would be otherwise caused when the stacked type piezoelectric/electrostrictive element 24 is used.

As described above, the driving force of the actuator section 204 is increased by using the stacked type piezoelectric/electrostrictive element 24, and thus it is possible to obtain the large displacement. Further, it is possible to realize the high resonance frequency by increasing the rigidity of the piezoelectric/electrostrictive device 10B itself. Thus, it is easy to achieve the high speed of the displacement action.

When the number of stages is increased, it is possible to increase the driving force of the actuator section 204. However, the electric power consumption is also increased in accordance therewith. Therefore, when the present invention is carried out, the number of stages may be appropriately determined depending on the way of use and the state of use. In the case of the piezoelectric/electrostrictive device 10B according to the second embodiment, the width of the thin plate section 16a, 16b (distance in the Y axis direction) is basically unchanged, even when the driving force of the actuator section 204 is increased, owing to the use of the stacked type piezoelectric/electrostrictive element 24. Therefore, the device is extremely preferred to make application, for example, to the actuator for the purpose of the ringing control and the positioning of the magnetic head

for the hard disk to be used in an extremely narrow gap.

5 The stacked type piezoelectric/electrostrictive element 24 is preferably formed at the following position with respect to the thin plate section 16a. That is, the forward end 208 of the multilayered member for constructing the stacked type piezoelectric/electrostrictive element 24 is disposed at the position not including at least the fixation section 22 as viewed in plan view (position included in the hole 12 formed between the movable section 20 and the fixation section 22 in the example shown in FIG. 25). The rearward end 209 of the multilayered member for constructing the stacked type piezoelectric/electrostrictive element 24 is disposed at the position including at least the fixation section 22 as viewed in plan view. The end 28a of the electrode 28 is formed at the position including at least the fixation section 22 as viewed in plan view, and the end 30a of the electrode 30 is formed at the position not including at least the fixation section 22 as viewed in plan view (position included in the hole 12 formed between the movable section 20 and the fixation section 22 as well in the example shown in FIG. 25).

10
15
20
25 The voltage is applied to the pair of electrodes 28, 30 via ends (hereinafter referred to as "terminals 28b, 30b") of the respective electrodes 28, 30 formed on the fifth layer of the piezoelectric/electrostrictive layer 30. The respective terminals 28b, 30b are formed to be separated from each other in such a degree that they can be

electrically insulated from each other.

The spacing distance D_k between the terminals 28b, 30b is preferably not less than 20 μm , and it is preferably not less than 50 μm when the thickness of the terminal 28b, 30b is 1 μm to 30 μm . The terminals 28b, 30b may be made of the same material as that of the internal electrodes 28, 30, or they may be made of a material different therefrom. For example, the same material may be used when the terminals 28b, 30b are sintered simultaneously with the piezoelectric/electrostrictive layer 26. The different materials may be used when the sintering is performed separately.

It is preferable for the end surface electrodes 28c, 30c that the internal electrodes 28, 30 and the piezoelectric/electrostrictive layer 26 are sintered, and then their end surfaces are subjected to, for example, grinding and polishing to effect the electric connection between the internal electrodes and the end surface electrodes. The material of the end surface electrodes 28c, 30c may be the same as, or different from that of the internal electrodes 28, 30. For example, it is preferable that platinum paste is utilized for the internal electrodes 28, 30, gold resinate is utilized for the outer surface electrode 28d, and gold paste is utilized for the end surface electrodes 28c, 30c and the terminals 28b, 30b. However, it is also possible to adopt approximately the same construction as that of the piezoelectric/electrostrictive

device according to the first embodiment described above.

In this arrangement, the piezoelectric/electrostrictive device 10B can be independently fixed by utilizing the surface other than the surface on which the terminals 28b, 30b are arranged. As a result, it is possible to obtain high reliability for both of the fixation of the piezoelectric/electrostrictive device 10B and the electric connection between the circuit and the terminals 28b, 30b. In this arrangement, the electric connection between the terminals 28b, 30b and the circuit is made, for example, by means of the flexible printed circuit, the flexible flat cable, and the wire bonding.

As described above, in the piezoelectric /electrostrictive device 10B according to the second embodiment, the actuator section 204 is constructed by securing the stacked type piezoelectric/electrostrictive element 24 onto the thin plate section 16a made of metal by the aid of the adhesive 202. Therefore, it is possible to greatly displace the thin plate section 16a (and 16b) even when the areal size of the stacked type piezoelectric/electrostrictive element 24 is not widened as viewed in plan view. Further, the thin plate section 16a (and 16b) is made of metal. Therefore, the device is excellent in strength and toughness, and it is possible to respond to the quick displacement action as well.

In other words, in the second embodiment, it is possible to sufficiently respond to the variation of

environment of use and the severe state of use. The device is excellent in shock resistance. It is possible to realize the long life time of the piezoelectric/electrostrictive device 10B, and it is possible to improve the handling performance of the piezoelectric/electrostrictive device 10B. Further, the thin plate section can be greatly displaced at a relatively low voltage. The rigidity of the thin plate section 16a (and 16b) is high, the film thickness of the actuator section 204 is thick, and the rigidity of the actuator section 204 is high. Accordingly, it is possible to achieve the realization of the high speed (realization of the high resonance frequency) of the displacement action of the thin plate section 16a (and 16b).

Usually, in order to drive, at a high speed, the actuator section 204 constructed by combining the thin plate section 16a and the piezoelectric/electrostrictive element 24 which makes strain deformation, it is necessary to increase the rigidity of the actuator section 204. In order to obtain large displacement, it is necessary to decrease the rigidity of the actuator section 204.

However, in the piezoelectric/electrostrictive device 10B according to the second embodiment, the thin plate sections 16a, 16b, which constitute the actuator section 204, are opposed to one another to provide the pair of thin plate sections 16a, 16b. The fixation section 22 is secured by the adhesive 200 between the respective rearward ends of the pair of thin plate sections 16a, 16b to construct the

multiple stage structure of the piezoelectric/electrostrictive element 24. The position of the piezoelectric/electrostrictive element 24, the material and the size of the constitutive members are appropriately selected to construct the piezoelectric/electrostrictive device 10B. Therefore, it is possible to effect the both of the contradicting characteristics described above. When the object, which has the substantially the same degree of size as that of the fixation section 22, intervenes between the open ends of the pair of thin plate sections 16a, 16b, the minimum resonance frequency of the structure is not less than 20 kHz. Further, the relative displacement amount concerning the object and the fixation section 22 can be not less than 0.5 μm at a substantial applied voltage of 30 V at a frequency which is not more than 1/4 of the resonance frequency.

As a result, it is possible to greatly displace the pair of thin plate sections 16a, 16b. Further, it is possible to achieve the realization of the high speed (realization of the high resonance frequency) of the displacement action of the piezoelectric/electrostrictive device 10B, especially of the pair of thin plate sections 16a, 16b.

In the piezoelectric/electrostrictive device 10B according to the second embodiment, the minute displacement of the piezoelectric/electrostrictive element 24 is amplified into the large displacement action by utilizing

the bending of the thin plate sections 16a, 16b, and it is transmitted to the movable section 20. Therefore, the movable section 20 can be greatly displaced with respect to the major axis m (see FIG. 14) of the piezoelectric /electrostrictive device 10B.

In the piezoelectric/electrostrictive device 10B according to the second embodiment, it is unnecessary that all of the parts are formed with the piezoelectric /electrostrictive material which is a fragile material having a relatively heavy weight. Therefore, the device has the following advantages. That is, the device has the high mechanical strength, and it is excellent in handling performance, shock resistance, and moisture resistance. Further, the operation of the device is scarcely affected by harmful vibration (for example, noise vibration and remaining vibration during high speed operation).

Further, as shown in FIG. 24, the forward ends of the pair of thin plate sections 16a, 16b are the open ends. Accordingly, when various members or parts are attached to the piezoelectric/electrostrictive device 10B, it is possible to utilize the forward ends of the pair of thin plate sections 16a, 16b. The member or the part can be attached in such a way that the member or the part is interposed by the forward ends. In this case, it is possible to provide a large attachment area for the member or the part, and it is possible to improve the attachment performance for the part. Further, the member or the part

to be attached is consequently included in the pair of thin plate sections 16a, 16b. Therefore, it is possible to decrease the size of the piezoelectric/electrostrictive device in the Y direction after attaching the member or the part. Thus, the device is advantageous to realize the compact size.

Of course, as shown in FIG. 25, when the movable section 20 is secured between the respective forward ends of the pair of thin plate sections 16a, 16b, then various members or parts are secured, for example, by the aid of an adhesive to the first principal surface of the movable section 20.

In the second embodiment, the forward end 208 of the multilayered member for constructing the stacked type piezoelectric/electrostrictive element 24 is disposed at the position not including at least the fixation section 22 as viewed in plan view. The rearward end of the multilayered member is disposed at the position including at least the fixation section 22 as viewed in plan view. The end 28a of the electrode 28 is disposed at the position including at least the fixation section 22 as viewed in plan view. The end 30a of the electrode 30 is disposed at the position not including the fixation section 22 as viewed in plan view.

For example, if the respective ends of the pair of electrodes 28, 30 are formed at the position included in the movable section 20, then it is feared that the displacement action of the pair of thin plate sections 16a, 16b is

restricted by the stacked type
piezoelectric/electrostrictive element 24, and it is
impossible to obtain the large displacement. However, in
the second embodiment, the foregoing positional relationship
is adopted. Therefore, it is possible to avoid the
inconvenience of the restriction of the displacement action
of the movable section 20, and it is possible to increase
the displacement amount of the pair of thin plate sections
16a, 16b.

Next, explanation will be made for preferred
illustrative constructions of the piezoelectric
/electrostrictive device 10B according to the second
embodiment. The preferred illustrative constructions are
approximately the same as those of the piezoelectric
/electrostrictive device according to the first embodiment
described above. Therefore, explanation will be made for
only the preferred illustrative constructions inherent in
the piezoelectric/electrostrictive device 10B according to
the second embodiment.

At first, in the piezoelectric/electrostrictive device
10B according to the second embodiment, the shape of the
device 10B is not the plate-shaped configuration like the
conventional one. When the movable section 20 is provided,
the movable section 20 and the fixation section 22 form the
rectangular parallelepiped-shaped configuration. The pair
of thin plate sections 16a, 16b are provided so that the
side surfaces of the movable section 20 and the fixation

section 22 are continuous to give the rectangular annular configuration. Therefore, it is possible to selectively enhance the rigidity of the piezoelectric/electrostrictive device 10B in the Y axis direction.

5 That is, in the piezoelectric/electrostrictive device 10B, it is possible to selectively generate only the action of the movable section 20 in the plane (in the XZ plane). It is possible to suppress the action of the pair of thin plate sections in the YZ plane (action in the so-called swaying direction).

10 It is desirable that the thin plate sections 16a, 16b are made of metal. The fixation section 22 and the movable section 20 may be made of materials of different types, but they are more preferably made of metal. For example, organic resin, brazing material, or solder may be used to glue the thin plate sections 16a, 16b to the fixation section 22 and glue the thin plate sections 16a, 16b to the movable section 20. However, it is more preferable to form an integrated structure formed by diffusion joining or
15 welding between metal materials. It is more desirable to use metal subjected to the cold rolling process, because of the high strength owing to the presence of a great degree of dislocation.

20 In the second embodiment, the stacked type
25 piezoelectric/electrostrictive element 24 is formed on only one thin plate section 16a. Therefore, the device can be produced inexpensively as compared with a device (modified

embodiment) in which the stacked type piezoelectric /electrostrictive elements 24a, 24b are formed on the pair of thin plate sections 16a, 16b respectively as shown in FIG. 30. Further, in the second embodiment, when the observation is made in a state in which the movable section 20 is secured, then the thin plate section 16a having the large thickness, on which the stacked type piezoelectric /electrostrictive element 24 is formed, is directly displaced, and the thin plate section 16b having the thin thickness, on which the stacked type piezoelectric/electrostrictive element 24 is not formed, is displaced in cooperation therewith. Accordingly, it is possible to cause the displacement to a greater extent.

The formation of the stacked type piezoelectric /electrostrictive element 24 on the thin plate section 16a can be realized by gluing the stacked type piezoelectric /electrostrictive element 24 to the thin plate section 16a, for example, with organic resin, brazing material, or solder. When the element is glued at a low temperature, it is desirable to use organic resin. When the element is allowed to be glued at a high temperature, it is preferable to use, for example, brazing material, solder, and glass. However, the coefficient of thermal expansion is generally differs among the thin plate section 16a, the stacked type piezoelectric/electrostrictive element 24, and the adhesive 202. Therefore, it is desirable that the gluing temperature is low in order not to generate any stress in the stacked

type piezoelectric/electrostrictive element 24 due to the difference in coefficient of thermal expansion. In the case of organic resin, the gluing can be generally effected at a temperature of not more than 180 °C. Therefore, organic resin is preferably adopted. More preferably, it is desirable to use a room temperature setting adhesive. When the fixation of the thin plate section 16a, 16b and the piezoelectric/electrostrictive element 24 is performed simultaneously with, or after the fixation of the movable section 20, the fixation section 22 and the thin plate section 16a, 16b, if the fixation section 22 or the movable section 20 has the open type structure, then it is possible to effectively reduce the strain which would be otherwise caused between the different types of materials.

In order not to exert any thermal stress on the stacked type piezoelectric/electrostrictive element 24, it is preferable that the stacked type piezoelectric /electrostrictive element 24 is glued to the thin plate section 16a with organic resin, and the fixation is performed in separate steps for the thin plate sections 16a, 16b, the fixation section 22, and the movable section 20.

As shown in FIG. 31, when the part of the piezoelectric/electrostrictive element 24 is located at the fixation section 22, it is preferable that $(1 - L_b/L_a)$ is not less than 0.4, and more preferably 0.5 to 0.8 provided that L_a represents a shortest distance concerning the pair of thin plate sections 16a, 16b between a boundary portion

with respect to the movable section 20 and a boundary
portion with respect to the fixation section 22, and L_b
represents a shortest distance of distances from the
boundary portion between the thin plate section 16a and the
movable section 20 to any one of the ends 28a, 30a of the
pair of electrodes 28, 30 of the stacked type
piezoelectric/electrostrictive element 24. If $(1 - L_b/L_a)$
is not more than 0.4, it is impossible to make large
displacement. When $(1 - L_b/L_a)$ is 0.5 to 0.8, it is easy to
successively achieve both of the displacement and the
resonance frequency. However, in this case, it is more
appropriate to use a structure in which the stacked type
piezoelectric/electrostrictive element 24 is formed on only
one thin plate section 16a. This fact also holds when the
part of the piezoelectric/electrostrictive element 24 is
located at the movable section 20.

It is preferable that the total thickness of the
stacked type piezoelectric/electrostrictive element 24 is
not less than 40 μm . If the total thickness is less than 40
 μm , it is difficult to glue the stacked type piezoelectric
/electrostrictive element 24 to the thin plate section 16a.
It is desirable that the total thickness is not more than
180 μm . If the total thickness exceeds 180 μm , it is
difficult to realize a compact size of the piezoelectric
/electrostrictive device 10B.

As for the portion of the stacked type piezoelectric
/electrostrictive element 24 to make contact with the thin

plate section 16a, when the metal such as brazing material and solder layer is used as the adhesive 202, it is preferable that the electrode layer exists at the lowermost layer in view of the wettability as shown in FIGS. 28 and 29. FIGS. 28 and 29 show the state in which the electrode film for constructing the second electrode 30 is arranged.

When the stacked type piezoelectric/electrostrictive element 24 as shown in FIG. 26 and FIG. 28 is glued to the thin plate section 16a by the aid of the metal layer such as the brazing material and the solder layer, it is preferable to chamfer the angular portion at which at least one electrode 28 exists, of the lower surface of the stacked type piezoelectric/electrostrictive element 24 as shown in FIG. 27 and FIG. 29, because of the following reason. That is, it is intended to prevent the pair of electrodes 28, 30 from formation of short circuit which would be otherwise formed via the metal layer and the thin plate section 16a. FIG. 27 is illustrative of a case in which two angular portions, at which the pair of electrodes 28, 30 exist, are chamfered. FIG. 29 is illustrative of a case in which an angular portion, at which the first electrode 28 exists, is chamfered.

Those preferably used as the adhesive 202 for gluing the stacked type piezoelectric/electrostrictive element 24 to the thin plate section 16a and the adhesive 200 for gluing the thin plate sections 16a, 16b, for example, to the fixation section 22 include two-part type reactive adhesives

such as those based on epoxy and isocyanate, instantaneous adhesives such as those based on cyanoacrylate, and hot melt adhesives such as those based on ethylene-vinyl acetate copolymer. Especially, it is preferable to use those having Shore D hardness of not less than 80 as the adhesive 202 for gluing the stacked type piezoelectric/electrostrictive element 24 to the thin plate section 16a.

It is desirable that an organic adhesive containing a filler such as metal and ceramics is used as the adhesive 202 for gluing the thin plate section 16a, 16b and the piezoelectric/electrostrictive element 24 (24a, 24b). In this case, it is desirable that the thickness of the adhesive 202 is not more than 100 μm , because of the following reason. That is, when the filler is contained, then the substantial thickness of the resin component is decreased, and it is possible to maintain a high hardness of the adhesive.

It is also preferable to use inorganic adhesives as the adhesive 200, 202, other than the organic adhesives described above. The inorganic adhesive includes, for example, glass, cement, solder, and brazing material.

On the other hand, as for the shape and the material quality for the thin plate sections 16a, 16b, it is enough to have the flexibility, with the mechanical strength of such a degree that no breakage is caused due to bending deformation. Metal is preferably adopted. In this case, as described above, it is preferable to use a metal material

which has the flexibility and which is capable of the bending displacement. Specifically, it is preferable to use a metal material which has a Young's modulus of not less than 100 GPa.

5 Preferably, it is desirable that the thin plate section 16a, 16b is made of an iron-based material such as various spring steel materials, marageing stainless steel materials, and stainless steel materials including, for example, austenite-based stainless steel materials such as SUS301, SUS304, AISI653, and SUH660, ferrite-based stainless steel materials such as SUS430 and SUS434, maltensite-based stainless steel materials such as SUS410 and SUS630, and semiaustenite-based stainless steel materials such as SUS631 and AISI632. Alternatively, it is desirable that the thin plate section 16a, 16b is made of a non-ferrous material such as superelastic titanium alloy represented by titanium-nickel alloy, brass, cupronickel, aluminum, tungsten, molybdenum, beryllium copper, phosphor bronze, nickel, nickel-iron alloy, and titanium.

20 Next, explanation will be made with reference to FIGS. 32 to 40 for several production methods for manufacturing the piezoelectric/electrostrictive device 10B according to the second embodiment.

25 In the third production method, as shown in FIG. 32, a rectangular hole 252 having a size of width: 1 mm \times length: 8 mm is firstly bored through a central portion of a stainless steel plate 250 having a size of width: 1.6 mm \times

length: 10 mm × thickness: 0.9 mm to manufacture a substrate 258 having a rectangular annular structure with support sections 254, 256 arranged on both sides of the hole 252 respectively.

5 After that, as shown in FIG. 33, a first stainless steel thin plate 260 having a size of width: 1.6 mm × length: 10 mm × thickness: 0.05 and a second stainless steel thin plate 262 having a size of width: 1.6 mm × length: 10 mm × thickness: 0.02 (see FIG. 35) are prepared.

10 After that, as shown in FIG. 33, the adhesive 202 (for example, an adhesive made of epoxy resin) is formed by the screen printing on a portion of the upper surface of the first stainless steel thin plate 260 on which the stacked type piezoelectric/electrostrictive element 24 is formed.
15 After that, as shown in FIG. 34, the stacked type piezoelectric/electrostrictive element 24 is glued to the first stainless steel thin plate 260 by the aid of the adhesive 202.

20 After that, as shown in FIG. 35, the adhesive 200 (for example, an adhesive made of epoxy resin) is formed by the screen printing on the respective support sections 254, 256 of the substrate 258.

25 After that, the first stainless steel thin plate 260, on which the stacked type piezoelectric/electrostrictive element 24 has been already formed, is glued to the first surface of each of the support sections 254, 256 by the aid of the adhesive 200. The second stainless steel thin plate

262 is glued to the second surface of each of the support sections 254, 256 by the aid of the adhesive 200. Further, the pressure is applied to the first and second stainless steel thin plates 260, 262 in a direction to interpose the substrate 258 to manufacture a master device block 270 shown in FIG. 36. The applied pressure is 0.1 to 10 kgf/cm².

After that, as shown in FIG. 36, the master device block 270 is cut into portions along cutting lines 272 to divide the block into the individual piezoelectric /electrostrictive devices 10B as shown in FIG. 25. The cutting process was performed by using a wire saw having a wire diameter of 0.1 mm and a spacing distance of 0.2 mm. When the wire saw is used, it is possible to prescribe substantially the same size for the width of the piezoelectric/electrostrictive element 24, the width of the thin plate section 16a, and the width of the adhesives 200, 202, although these components are made of different materials respectively.

Next, in the fourth production method, as shown in FIG. 37, a rectangular hole 252 having a size of width: 1 mm × length: 8 mm is bored through a central portion of a stainless steel plate 250 having a size of width: 1.6 mm × length: 10 mm × thickness: 0.9 mm to manufacture a substrate 258 having a rectangular annular structure with support sections 254, 256 arranged on both sides of the hole 252 respectively.

After that, the adhesive 200 (for example, an adhesive

made of epoxy resin) is formed by the screen printing on the respective support sections 254, 256 of the substrate 258.

After that, as shown in FIG. 38, a first stainless steel thin plate 260 having a size of width: 1.6 mm × length: 10 mm × thickness: 0.05 is glued to the first surface of each of the support sections 254, 256 by the aid of the adhesive 200. A second stainless steel thin plate 262 having a size of width: 1.6 mm × length: 10 mm × thickness: 0.02 is glued to the second surface of each of the support sections 254, 256 by the aid of the adhesive 200. Further, the pressure is applied to the first and second stainless steel thin plates 260, 262 in a direction to interpose the substrate 258. The applied pressure is 0.1 to 10 kgf/cm².

After that, the adhesive 202 (for example, an adhesive made of epoxy resin) is formed by the screen printing on a portion of the upper surface of the first stainless steel thin plate 260 on which the stacked type piezoelectric /electrostrictive element 24 is formed.

After that, as shown in FIG. 40, the stacked type piezoelectric/electrostrictive element 24 is glued to the first stainless steel thin plate 260 by the aid of the adhesive 202 to manufacture a master device block 270.

After that, as shown in FIG. 36, the master device block 270 is cut into portions along cutting lines 272 to divide the block into the individual piezoelectric /electrostrictive devices 10B as shown in FIG. 25.

5 A part (for example, the fixation section 22) of the piezoelectric/electrostrictive device 10B produced in accordance with the first and second production methods was fixed. A bias voltage of 15 V and a sine wave voltage of ± 15 V were applied between the pair of electrodes 28, 30 of the stacked type piezoelectric/electrostrictive element 24 to measure the displacement of the movable section 20. As a result, the displacement was $\pm 1.2 \mu\text{m}$. The frequency was swept with a sine wave voltage of ± 0.5 V to measure the minimum resonance frequency to exhibit the maximum displacement. As a result, the minimum resonance frequency was 50 kHz.

10
15
20
25 In the third and fourth production methods described above, the substrate 258 is constructed to have the rectangular annular structure having the support section 254 to be formed into the movable section 20 thereafter and the support section 256 to be formed into the fixation section 22 thereafter. Alternatively, as shown in FIG. 41, a rectangular annular structure is also available, in which a hole 252 is widened to have a frame-shaped section 254a for supporting first and second stainless steel thin plates 260, 262 (section for substantially defining the thickness of a portion to allow at least the movable section 20 to intervene thereafter) and a support section 256 to be formed into the fixation section 22 thereafter.

In this case, the substrate 258 is secured by the aid of the adhesive 200 so that the substrate 258 is interposed

between the first and second stainless steel thin plates 260, 262 to manufacture a master device block 270 similar to one shown in FIG. 36, followed by being cut along cutting lines 272 as shown in FIG. 36. Accordingly, as shown in FIG. 44, for example, it is possible to produce a piezoelectric/electrostrictive device in which the movable section 20 does not exist between the forward ends of the thin plate sections 16a, 16b.

Next, explanation will be made with reference to FIGS. 42 to 46 for a fifth production method which is different from the third and fourth production methods described above.

The fifth production method is also applicable to a case in which support sections 254, 256 are glued to a first stainless steel thin plate 260 and a second stainless steel thin plate 262 to manufacture a master device block 270 in the same manner as in the third and fourth production methods described above, followed by being divided into individual piezoelectric/electrostrictive devices. The fifth production method is also applicable to a case in which the piezoelectric/electrostrictive device 10B is produced by securing the fixation section 22 (and the movable section 20, if desirable) prepared separately to a unit prepared separately as each actuator section 204 comprising the stacked type piezoelectric/electrostrictive element 24a, 24b formed on the thin plate sections 16a, 16b.

In the following description, the support section 254

to be formed into the movable section 20 thereafter and the movable section 20 are conveniently referred to as "movable section 20", the support section 256 to be formed into the fixation section 22 thereafter and the fixation section 22 are conveniently referred to as "fixation section 22", and the first and second stainless steel thin plates 260, 262 to be formed into the thin plate sections 16a, 16b thereafter and the thin plate sections 16a, 16b are conveniently referred to as "thin plate sections 16a, 16b".

As shown in FIG. 42, when the thin plate sections 16a, 16b are glued by the aid of adhesive 200 to the movable section 20 and the fixation section 22 respectively, if the adhesive having fluidity is used, then it is preferable to provide bumps 280am, 280an, 280bm, 280bn for the respective thin plate sections 16a, 16b in order to define the places for forming the adhesive 200. Of course, when the adhesive having high viscosity is used, it is unnecessary to provide such a bump. The bumps 280am, 280an, 280bm, 280bn may be also formed by stacking plate-shaped members.

FIG. 43 is illustrative of a case in which the adhesive having high fluidity is used as the adhesive 200 for gluing the movable section 20 and the respective thin plate sections 16a, 16b, and the adhesive having high viscosity is used as the adhesive 200 for gluing the fixation section 22 and the respective thin plate sections 16a, 16b, wherein the bumps 280an, 280bn are provided at portions of the thin plate sections 16a, 16b for which the adhesive having high

fluidity is used.

FIG. 44 is illustrative of a case in which the adhesive having high viscosity is used as the adhesive 200 for gluing the fixation section 22, and the thin plate sections 16a, 16b, depicting a structure in which the bump 280am, 280an, 280bm, 280bn as described above is not provided.

FIG. 45 is illustrative of a case in which the adhesive having high fluidity is commonly used as the adhesive 200 for gluing the fixation section 22, the movable section 20, and the thin plate sections 16a, 16b, especially depicting an example which is provided with projections 282am, 282an, 282bm, 282bn for comparting regions for forming the adhesive 200 on the thin plate sections 16a, 16b.

As shown in FIG. 46 concerning the example shown in FIG. 42, it is also preferable that each of the size of the fixation section 22 and the movable section 20, especially the areal size of the surface opposed to the bump 280am, 280bm of each of the thin plate sections 16a, 16b concerning the fixation section 22 is made to be larger than the areal size of the bump 280am, 280bm. Also, the areal size of a surface opposed to the bump 280an, 280bn of each of the thin plate sections 16a, 16b concerning the movable section 20 is made to be larger than the areal size of the bump 280an, 280bn. Accordingly, the substantial driving portion (portion between the bumps 280am and 280an and portion between the bumps 280bm and 280bn) of the thin plate sections 160a, 160b can be defined by the bump 280am, 280an,

280bm, 280bn. As shown in FIG. 42, when the areal size of the surface opposed to the bump 280am, 280bm of each of the thin plate sections 16a, 16b concerning the fixation section 22 is made to be substantially the same as the areal size of the bump 280am, 280bm, and the areal size of the surface opposed to the bump 280an, 280bn of each of the thin plate sections 16a, 16b concerning the movable section 20 is made to be substantially the same as the areal size of the bump 280an, 280bn, it is feared that the dispersion in size concerning the fixation section 22 and the bump 280am, 280bm, and the dispersion in size concerning the movable section 20 and the bump 280an, 280bn affect the length of the substantial driving portion. FIG. 46 is illustrative of the case in which the size of the fixation section 22 is increased toward the movable section 20. Alternatively, it is also preferable that the size of the fixation section 22 is increased outwardly oppositely to the direction toward the movable section 20. Similar structural variations are available with regard to the movable section 20.

In FIGS. 42 to 46, the bumps 280am, 280bm, 280an, 280bn or the projections 282am, 282bm, 282an, 282bn and the thin plate sections 16a, 16b are integrated with the thin plate sections. However, these components may be provided by stacking appropriately processed plates by the aid of an adhesive, in the same manner as in FIG. 19 or FIG. 23. In the case of the provision by means of the integration, the bumps 280am, 280bm, 280an, 280bn or the projections 282am,

282bm, 282an, 282bn can be integrally provided for the thin plate sections 16a, 16b formed as a result of etching or cutting a plate member.

5 The embodiment described above is illustrative of the case in which the adhesive 200, 202 is formed by means of the screen printing. Alternatively, it is possible to use, for example, dipping, dispenser, and transfer.

10 Next, explanation will be made with reference to FIGS. 47 to 52 for various illustrative constructions concerning the adhesive 202 which intervenes, for example, between the thin plate section 16a and the stacked type piezoelectric /electrostrictive element 24 and the adhesive 200 which intervenes between the thin plate sections 16a, 16b, the movable section 20, and the fixation section 22.

15 ~~At first, in the first technique shown in FIG. 47, a~~
20 ~~large number of holes 290 are provided through the thin~~
~~plate section 16a. The stacked type piezoelectric~~
~~/electrostrictive element 24 is glued to a portion at which~~
~~the holes 290 are provided, by the aid of the adhesive 202.~~
25 In this arrangement, the adhesive 202 enters the inside of the holes 290. Therefore, the adhesion area is substantially increased, and it is possible to use a thin thickness of the adhesive 202. It is preferable that the thickness of the adhesive 202 is not more than 5 % of the total thickness of the stacked type piezoelectric/electrostrictive element 24 and not less than a thickness of such a degree that the thermal stress due to

INS.
B23
cancel.

~~the difference in coefficient of thermal expansion between the thin plate section 16a and the adhesive 202 can be absorbed.~~

5 It is preferable that the diameter of the hole 290 is 5 μm to 100 μm . The arrangement pattern may be either a matrix form or a zigzag arrangement. Of course, a plurality of holes 290 may be arranged in one array. It is preferable that the arrangement pitch of the holes 290 is 10 μm to 200 μm . Alternatively, recesses (bores) may be used in place of the holes 290. In this arrangement, it is preferable that the diameter of the bore is 5 μm to 100 μm . The arrangement pattern may be either a matrix form or a zigzag arrangement. It is preferable that the arrangement pitch of the bores is 10 μm to 200 μm . Especially, in the case of the recess (bore), for example, it is also preferable to use a rectangular configuration as viewed in plan view with its opening area which is slightly smaller than the projection area of the piezoelectric/electrostrictive element 24 onto the thin plate section 16a. Those adoptable as the technique for forming the holes 290 or the bores in the thin plate section 16a include, for example, etching, laser machining, stamping, drill machining, electric discharge machining, and ultrasonic machining.

25 In the second technique shown in FIG. 48, the surface 292 of a portion of the thin plate section 16a, on which a stacked type piezoelectric/electrostrictive element 24 is formed, is roughened by means of the blast treatment, the

etching treatment, or the plating treatment. In this arrangement, the lower surface 294 of the stacked type piezoelectric/electrostrictive element 24 is also roughened. Accordingly, the adhesion area is substantially increased. Therefore, it is possible to use a thin thickness of the adhesive 202.

FIG. 48 is illustrative of the case in which the surface of the thin plate section 16a and the lower surface of the piezoelectric/electrostrictive element 24 (surface opposed to the thin plate section 16a) are roughened. However, it is enough that the surface having the small adhesion force with respect to the adhesive 202 is roughened. A sufficient effect is obtained, for example, even when only the surface of the thin plate section 16a is roughened. The surface roughness is preferably $R_a = 0.1 \mu\text{m}$ to $5 \mu\text{m}$, and more preferably $0.3 \mu\text{m}$ to $2 \mu\text{m}$, for example, as estimated by the center line average roughness.

In the third technique shown in FIG. 49, a curvature 296 is provided for the stick-out shape of the adhesive 200, especially for the stick-out shape of the adhesive 200 toward the hole (hole 252 of the substrate 258) formed by the inner walls of the thin plate sections 16a, 16b, the inner wall 20a of the movable section 20, and the inner wall 22a of the fixation section 22. In this arrangement, it is preferable that the radius of curvature is not less than 0.05 mm and up to the extent that the stick-out shape is linear, or the stick-out shape includes a linear portion.

The formation of the curvature 296 for the stick-out portion of the adhesive 200 can be realized, for example, by inserting a cylindrical core member into the hole 252 before curing the adhesive 200. Practically, the control is made based on the use of the application amount and the physical property of the adhesive 200 so that the stick-out shape is at least not convex.

Accordingly, the inner wall 20a of the movable section 20, the inner wall 22a of the fixation section 22, and the inner walls of the respective thin plate sections 16a, 16b are also used as the adhesion surfaces. Therefore, the adhesion area is increased, and it is possible to increase the adhesion strength. Further, it is possible to effectively disperse the concentration of the stress on the joined portions (angular portions) between the inner wall 22a of the fixation section 22 and the inner walls of the respective thin plate sections 16a, 16b.

In the fourth technique shown in FIG. 50, angular portions opposed to the fixation section 22, of angular portions of the movable section 20, and/or angular portions opposed to the movable section 20, of angular portions of the fixation section 22 are chamfered respectively to form tapered surfaces 298. The stick-out amount of the adhesive 200 can be stabilized by appropriately adjusting the radius of curvature and the angle of the chamfering. It is possible to suppress the local dispersion of the adhesion strength, and it is possible to improve the yield.

The following method is preferably used to chamfer the angular portion. That is, for example, the cutting and the polishing are performed beforehand for the portions to be formed into the angular portions of the first support section 264 and the second support section 256 to form the tapered surfaces 298 before the assembling. Of course, the chamfering may be performed after the assembling. In this case, for example, the laser machining, the ultrasonic machining, or the sandblast is preferably adopted.

The fifth technique shown in FIG. 51 relates to the punching out process which is usually performed, for example, when the thin plate sections 16a, 16b are manufactured. In this case, burrs 300 are formed. The formed burrs 300 may be removed before the assembling. However, they may be allowed to remain as they are. In this case, it is preferable that the directions of the formed burrs 300 are regulated, for example, in consideration of the handling and the adhesion directions of the respective members as well as the easiness of control of the amount of the adhesive. The example shown in FIG. 51 is illustrative of a state in which the burrs 300 of the thin plate sections 16a, 16b are directed outwardly.

In the sixth technique shown in FIG. 52, the thickness of the first thin plate section 16a is made to be larger than the thickness of the second thin plate section 16b as described above. In the case of the use as the actuator section 204 and the sensor, the stacked type

piezoelectric/electrostrictive element 24 is preferably formed on the first thin plate section 16a.

Other techniques are also available. For example, when the stacked type piezoelectric/electrostrictive element 24 is glued to the thin plate section 16a, 16b by the aid of the adhesive 202, for example, it is preferable that a ZrO_2 layer is allowed to intervene as an underlying layer for the lower surface of the stacked type piezoelectric /electrostrictive element 24.

When the stainless steel thin plates 260, 262 (for example, see FIG. 33) are used as the thin plate sections 16a, 16b, it is preferable that the longitudinal direction of the thin plate sections 16a, 16b is approximately coincident with the direction of the cold rolling applied to the stainless steel thin plates 260, 262.

It is preferable that the piezoelectric /electrostrictive layer 26 for constructing the stacked type piezoelectric/electrostrictive element 24 is stacked in about three layers to ten layers.

The piezoelectric/electrostrictive devices 10A, 10B described above can be utilized as the active device including, for example, various transducers, various actuators, frequency region functional parts (filters), transformers, vibrators, resonators, oscillators, and discriminators for the communication and the power generation, as well as the sensor element for various sensors including, for example, ultrasonic sensors,

acceleration sensors, angular velocity sensors, shock sensors, and mass sensors. Especially, the piezoelectric /electrostrictive devices 10A, 10B described above can be preferably utilized for various actuators to be used for the mechanism for adjusting the displacement and the positioning and for adjusting the angle for various precision parts such as those of optical instruments and precision mechanical equipments.

It is a matter of course that the piezoelectric /electrostrictive device and the method for producing the same according to the present invention are not limited to the embodiments described above, which may be embodied in other various forms without deviating from the gist or essential characteristics of the present invention.